
HERO B

108791.21 + 108917.99

HERO B: ANG.SX 50W 2.7K 589 PUSH CAP + HERO: ANG.2 DIFF.MICROPRISM.L589





Features

Use: Indoor
Type of installation: SUSPENDED
Emission: DIRECT/INDIRECT
Optics: MICROPRISMATIZED
Colour: CAPPUCCINO
Dimming: PUSH
Emergency: NO
L: 589x589mm
A: 53mm
H: 92mm
Made in: ITALY
Warranty: 5 years
Weight: 3.3kg

Tech data

Luminaire input power: 57W
Luminaire luminouse flux: 4853lm
Indirect luminous flux: 2767lm
IP: 40
Insulation class: I
No. of driver per product: 2
Supply voltage: 220-240V 50/60Hz
UGR: <19
SELV: Sì

Source

Light source: LED
Source power: 50W
Colour temperature: 2700K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

HERO B: View more product info

Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV Gmbh


This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 9/6/2026, 17:42:35

HERO B

108791.21 + 108917.99

HERO B: ANG.SX 50W 2.7K 589 PUSH CAP + HERO: ANG.2 DIFF.MICROPRISM.L589





Features

Use: Indoor
Optics: MICROPRISMATIZED
L: 589x589mm
A: 48mm
H: 6mm
Made in: ITALY
Warranty: 5 years
Weight: 0.2kg

Tech data

IP: 40
UGR: <19

Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2012).

Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV Gmbh

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 9/6/2026, 17:42:35

HERO B

108791.21 + 108917.99

HERO B: ANG.SX 50W 2.7K 589 PUSH CAP + HERO: ANG.2 DIFF.MICROPRISM.L589

COMPLETION ACCESSORIES

	HERO B: MOD.CIECO 250 CAP	**1087A3.21**
	HERO B: MOD.CIECO ANG.SX 150 CAP	**1087A4.21**
	HERO B: MOD.CIECO ANG.DX 150 CAP	**1087A5.21**
	HERO B: MOD.CIECO 1120 CAP	**1087A6.21**
	HERO B: MOD.CIECO 1400 CAP	**1087A7.21**
	HERO B: MOD.CIECO 1680 CAP	**1087A8.21**

MOUNTING ACCESSORIES

	HERO B: KIT COPPIA CAVI SOSP. 5 M	**1087B2.99**
	KIT ALIMENTAZIONE L1200 5P BIA	**108921.01**
	KIT ALIMENTAZIONE L1200 5P CAP	**108921.21**
	KIT ALIMENTAZIONE L3000 5P BIA	**108922.01**

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 9/6/2026, 17:42:35

HERO B

108791.21 + 108917.99

HERO B: ANG.SX 50W 2.7K 589 PUSH CAP + HERO: ANG.2 DIFF.MICROPRISM.L589



KIT ALIMENTAZIONE L3000 5P CAP **108922.21**

Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV Gmbh

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 9/6/2026, 17:42:35