


# HERO C

**108809.01 + 108903.99**

HERO C: 36W 4K 1680 BIA + HERO: DIFF. OPALE PER 1680






## Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: OPAL
Colour: WHITE
Dimming: NO
Emergency: NO
L: 1680mm
A: 61mm
H: 68mm
Made in: ITALY
Warranty: 5 years
Weight: 4.2kg

## Tech data

Luminaire input power: 40.5W
Luminaire luminouse flux: 3220lm
IP: 40
Insulation class: I
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
SELV: Sì

## Source

Light source: LED
Source power: 36W
Colour temperature: 4000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L90 B10

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

## Standards

Photobiological risk: RISK GROUP 0Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

HERO C: View more product info

Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV Gmbh



**This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.**
**Last update: 9/6/2026, 18:02:00**

# HERO C

**108809.01 + 108903.99**

HERO C: 36W 4K 1680 BIA + HERO: DIFF. OPALE PER 1680




## Features

Optics: OPAL
L: 1680mm
A: 48mm
H: 6mm
Made in: ITALY
Warranty: 5 years
Weight: 0.4kg

## Tech data

IP: 40
SELV: No













**This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.**
**Last update: 9/6/2026, 18:02:00**

# HERO C

**108809.01 + 108903.99**

HERO C: 36W 4K 1680 BIA + HERO: DIFF. OPALE PER 1680

**COMPLETION ACCESSORIES**

| | | |
|---|---|---|
|  | HERO C: COPPIA TESTATE BIA | **108860.01** |
|  | HERO C: MOD.CIECO 250 BIA | **108852.01** |
|  | HERO C: MOD.CIECO ANG.DX 150 BIA | **108854.01** |
|  | HERO: TESTATA OPALE PER SCHERMO TL 2PZ | **108930.99** |
|  | HERO C: MOD.CIECO 1120 BIA | **108855.01** |
|  | HERO C: MOD.CIECO 1680 BIA | **108857.01** |
|  | HERO C: MOD.CIECO 1400 BIA | **108856.01** |

Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV Gmbh



**This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.**
**Last update: 9/6/2026, 18:02:00**