


HERO C

108813.02 + 108908.99

HERO C: ANG.SX 24W 2.7K 593 NE + HERO: ANG.N.2 DIFF.OPALE PER 589







Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: OPAL
Colour: BLACK
Dimming: NO
Emergency: NO
L: 589x589mm
A: 61mm
H: 68mm
Made in: ITALY
Warranty: 5 years
Weight: 2.1kg

Tech data

Luminaire input power: 28.5W
Luminaire luminouse flux: 1909lm
IP: 40
Insulation class: I
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
SELV: Sì

Source

Light source: LED
Source power: 24W
Colour temperature: 2700K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

HERO C: View more product info

Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV Gmbh

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 9/6/2026, 18:00:40

HERO C

108813.02 + 108908.99


HERO C: ANG.SX 24W 2.7K 593 NE + HERO: ANG.N.2 DIFF.OPALE PER 589

Features

Use: Indoor
Optics: OPAL
L: 589x589mm
A: 48mm
H: 6mm
Made in: ITALY
Warranty: 5 years
Weight: 0.2kg

Tech data

IP: 40











This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 9/6/2026, 18:00:40

HERO C

108813.02 + 108908.99

HERO C: ANG.SX 24W 2.7K 593 NE + HERO: ANG.N.2 DIFF.OPALE PER 589

COMPLETION ACCESSORIES

	HERO C: MOD.CIECO 250 NE	**108852.02**
	HERO C: MOD.CIECO ANG.SX 150 NE	**108853.02**
	HERO C: MOD.CIECO ANG.DX 150 NE	**108854.02**
	HERO C: MOD.CIECO 1120 NE	**108855.02**
	HERO C: MOD.CIECO 1400 NE	**108856.02**
	HERO C: MOD.CIECO 1680 NE	**108857.02**

Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV Gmbh

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 9/6/2026, 18:00:40