



Features

Use: Indoor
Type of installation: RECESSED INTO BRICKWORK, RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: TRANSPARENT
Colour: WHITE
Dimming: WITH ACCESSORY
Emergency: NO
L: 37mm
A: 37mm
H: 34mm
D: 32-35mm
Warranty: 5 years
Weight: 0.12kg

Tech data

Luminaire luminouse flux: 110lm
IP: 65
Insulation class: III
Supply voltage: DC 700 MA

Source

Light source: LED
Source power: 2W
Colour temperature: 4000K
LED lifespan: 30000h L70 B20


Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)



MOUNTING ACCESSORIES



NEWSTEP: PLACCA MURALE

109405.99

ELECTRICAL ACCESSORIES



ALIM. LED 4W/700MA 2.5-6V

101322.99

DIMMABLE ACCESSORIES



ALIM. LED 25W 700MA/2-36V DALI/PUSH

101336.99