


HALOS SPOT

109704.01

novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Features

Use: Indoor
Type of installation: SUSPENDED
Emission: DIRECT
Optics: OPALE/SPOT
Beam: 40°
Colour: WHITE
Dimming: WITH ACCESSORY
Emergency: NO
L: Ø 962mm
A: 40mm
H: 50mm
Made in: ITALY
Warranty: 5 years
Weight: 7.5kg

Tech data

Luminaire input power: 85.2W
Luminaire luminous flux: 6314lm
IP: 20
Insulation class: III
Supply voltage: MAX 1.8A+0.5A
SELV: No

Source

Light source: LED
Source power: 80W
Colour temperature: 3000K
CRI: >90
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)





Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 8/4/2025, 11:40:28

MOUNTING ACCESSORIES

	HALOS: ROSONE ALIM. REMOTA BIA	105157.01
	HALOS: ROSONE DOPPIA ALIM. REMOTA BIA	105158.01

ELECTRICAL ACCESSORIES

	HALOS SPOT: COPPIA ALIM. ON/OFF REM.	109713.99
	HALOS SPOT: COPPIA ALIM. DALI/PUSH REM.	109714.99
	HALOS SPOT: ROSONE ON/OFF BI	109715.01
	HALOS SPOT: ROSONE DALI/PUSH BI	109716.01
	HALOS SPOT: ROSONE-N ON/OFF BI	109717.01
	HALOS SPOT: ROSONE-N DALI/PUSH BI	109718.01