

Features

Use: Indoor
Type of installation: RECESSED, SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: OPAL
Colour: WHITE
Dimming: WITH ACCESSORY
Emergency: NO
A: 40mm
H: 40mm
ø: 962mm
Made in: ITALY
Warranty: 5 years
Weight: 4.2kg

Tech data

Luminaire input power: 44.8W
Luminaire luminous flux: 3239lm
IP: 40
Insulation class: III
Supply voltage: MAX 1.8A
UGR: <19
SELV: No

Source

Light source: LED
Source power: 42W
Source luminous flux: 5932lm
Colour temperature: 3000K
CRI: >90
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

COMPLETION ACCESSORIES

	ARK/HALOS: KIT GIUNZIONE PROFILI BIA	109809.01
---	--------------------------------------	-----------


MOUNTING ACCESSORIES

	CAVO ALIMENTAZIONE L=3000 2X1 BIANCO	109001.01
---	--------------------------------------	-----------

	HALOS: ROSONE DOPPIA ALIM. REMOTA BIA	105158.01
---	---------------------------------------	-----------

	HALOS: KIT 4 CAVI SOSPENSIONE L.3000	105159.99
---	--------------------------------------	-----------

	HALOS: ROSONE ALIM. REMOTA BIA	105157.01
---	--------------------------------	-----------

	ARK: KIT INCASSO PER 962	109807.99
--	--------------------------	-----------

ELECTRICAL ACCESSORIES

	HALOS: ROSONE-N DOPPIA ALIM ON/OFF BIA	105155.01
---	--	-----------

	HALOS: ROSONE-N ALIM. ON/OFF BIA	105151.01
---	----------------------------------	-----------

	HALOS: ALIMENTATORE ON/OFF	105147.99
---	----------------------------	-----------

DIMMABLE ACCESSORIES



HALOS: ROSONE-N ALIM. DALI/PUSH BIA

105152.01



HALOS: ALIMENTATORE DALI/PUSH

105148.99



HALOS: ROSONE-N DOPPIA ALIM D/PUSH BIA

105156.01