



## Features

Use: Indoor  
Type of installation: WALL  
Emission: DIRECT/INDIRECT  
Optics: OPAL  
Colour: CAFFE  
Dimming: PUSH, DALI  
Emergency: NO  
L: 600mm  
A: 37mm  
H: 106mm  
Made in: ITALY  
Warranty: 5 years

## Tech data

Luminaire input power: 26W  
Luminaire luminous flux: 1510lm  
IP: 40  
Insulation class: I  
No. of driver per product: 1  
Supply voltage: 220-240V 50/60Hz  
SELV: Sì

## Source

Light source: LED  
Source power: 2x12W  
Source luminous flux: 3804lm  
Colour temperature: 4000K  
CRI: >90  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

## COMPLETION ACCESSORIES

---



RECTA: COPPIA TESTATE CF

**111428.20**