



Features

Use: Indoor
Type of installation: WALL
Emission: DIRECT/INDIRECT
Optics: OPAL
Colour: CAFFE
Dimming: PUSH, DALI
Emergency: NO
L: 1200mm
A: 37mm
H: 106mm
Made in: ITALY
Warranty: 5 years

Tech data

Luminaire input power: 50W
Luminaire luminous flux: 3020lm
IP: 40
Insulation class: I
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
SELV: Sì

Source

Light source: LED
Source power: 2x23W
Source luminous flux: 7608lm
Colour temperature: 4000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[RECTA: View more product info](#)

COMPLETION ACCESSORIES



RECTA: COPPIA TESTATE CF

111428.20