



Features

Use: Indoor
Type of installation: SUSPENDED
Emission: DIRECT
Optics: SPOT
Colour: DARK GREY
H: 200mm
Ø: 40mm
Made in: EU
Warranty: 5 years


Tech data

Insulation class: I
Supply voltage: 220-230V 50/60 Hz

Source

Socket: GU10 mini Ø35mm (lamp not included)
Source power: MAX 10W LED

[View more product info](#)



SCREENS



DIFFUSORE D.40 OPALE X SPOT BI/NE/LG/DG

112901.99

MOUNTING ACCESSORIES



ROSONE CIRCOLARE 3 X D. 200 DARK GREY

112908.24



ROSONE LINEA. 12X ORIZZONTALI L.780 BIAN

112916.01



ROSONE CIRCOLARE 3 X D. 200 NERO

112908.02



RACCORDO PASSACAVO SENZA FORO 5PZ BIANCO

112920.01



ROSONE TONDO 4X ORIZZONTALI D180 BI

112913.01



ROSONE INCASSO DIAM. 40 NERO

112906.02



ROSONE TONDO 4X ORIZZONTALI D180 NE

112913.02



ROSONE LINEARE 3 X L=620 NERO

112907.02



ROSONE CIRCOLARE 3 X D. 200 LIGHT GREY

112908.23



ROSONE INCASSO DIAM. 40 BIANCO

112906.01

COLLINS SP

111801.24

novalux
ITALIAN LIGHTING DESIGN SINCE 1948

ROSONE INCASSO DIAM. 40 LIGHT GREY

112906.23



Novalux S.r.l. via Marzabotto, 2 40050 Fano di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 8/4/2025, 11:34:41

	ROSONE TONDO 12X ORIZZONTALI D300 BI	112914.01
	RACCORDO PASSACAVO SENZA FORO 5PZ NERO	112920.02
	ROSONE PLAFONE D. 55 NERO	112905.02
	ROSONE PLAFONE D. 55 LIGHT GREY	112905.23
	ROSONE LINEARE 3 X L=620 LIGHT GREY	112907.23
	ROSONE PLAFONE D. 55 BIANCO	112905.01
	ROSONE LINEA. 12X VERTICALI L.1500 NERO	112917.02
	ROSONE PLAFONE D. 55 DARK GREY	112905.24
	ROSONE LINEARE 3 X L=620 BIANCO	112907.01

LAMPS

	LAMP. LED GU10 MINI 3000K 3W 60°	441400003
--	----------------------------------	------------------