



Features

Use: Indoor
Type of installation: SUSPENDED
Emission: DIRECT
Optics: SPOT
Colour: LIGHT GREY
H: 350mm
ø: 65mm
Made in: EU
Warranty: 5 years


Tech data

Insulation class: I
Supply voltage: 220-230V 50/60 Hz












Source

Socket: GU10 (lamp not included)
Source power: MAX 10W LED

[View more product info](#)



MOUNTING ACCESSORIES

	ROSONE PLAFONE D. 55 BIANCO	112905.01
	ROSONE PLAFONE D. 55 NERO	112905.02
	ROSONE PLAFONE D. 55 LIGHT GREY	112905.23
	ROSONE PLAFONE D. 55 DARK GREY	112905.24
	ROSONE INCASSO DIAM. 40 BIANCO	112906.01
	ROSONE INCASSO DIAM. 40 NERO	112906.02
	ROSONE INCASSO DIAM. 40 LIGHT GREY	112906.23
	ROSONE INCASSO DIAM. 40 DARK GREY	112906.24
	ROSONE LINEARE 3 X L=620 BIANCO	112907.01
	ROSONE LINEARE 3 X L=620 NERO	112907.02
	ROSONE LINEARE 3 X L=620 LIGHT GREY	112907.23
	ROSONE LINEARE 3 X L=620 DARK GREY	112907.24

CRYSTAL

111901.23

novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 14/11/2024, 18:20:29



ROSONE CIRCOLARE 3 X D. 200 BIANCO

112908.01



ROSONE CIRCOLARE 3 X D. 200 NERO

112908.02



ROSONE CIRCOLARE 3 X D. 200 LIGHT GREY

112908.23



ROSONE CIRCOLARE 3 X D. 200 DARK GREY

112908.24