



Features

Use: Indoor
Type of installation: SUSPENDED
Emission: DIRECT
Optics: SPOT
Colour: DARK GREY
H: 350mm
ø: 55mm
Made in: EU
Warranty: 5 years


Tech data

IP: 20
Insulation class: I
Supply voltage: 220-230V 50/60 Hz

Source

Socket: GU10 (lamp not included)
Source power: MAX 10W LED

[CRYSTAL : View more product info](#)



MOUNTING ACCESSORIES

	BRIDGE SYSTEM: RACCORDO PASSACAVO SENZA FORO 5PZ BIANCO	112920.01
	BRIDGE SYSTEM: RACCORDO PASSACAVO SENZA FORO 5PZ NERO	112920.02
	BRIDGE SYSTEM: RACCORDO PASSACAVO CON FORO 5PZ BIANCO	112921.01
	BRIDGE SYSTEM: RACCORDO PASSACAVO CON FORO 5PZ NERO	112921.02
	ROSONE TONDO 4X ORIZZONTALI D180 BI	112913.01
	ROSONE TONDO 4X ORIZZONTALI D180 NE	112913.02
	ROSONE TONDO 12X ORIZZONTALI D300 BI	112914.01
	ROSONE TONDO 12X ORIZZONTALI D300 NE	112914.02
	ROSONE TONDO 12X VERTICALI D350 BI	112915.01
	ROSONE TONDO 12X VERTICALI D350 NE	112915.02
	ROSONE LINEA. 12X ORIZZONTALI L.780 BIANCO	112916.01



ROSONE LINEA. 12X ORIZZONTALI L.780 NERO

112916.02

ROSONE LINEA. 12X VERTICALI L.1500 BIAN

112917.01

ROSONE LINEA. 12X VERTICALI L.1500 NERO

112917.02

BRIDGE SYSTEM: ADAT. ALL-TRACK ELET/MEC ON/OFF C/MORS B

112922.01

BRIDGE SYSTEM: ADAT. ALL-TRACK ELET/MEC ON/OFF C/MORS N

112922.02

ROSONE PLAFONE D. 55 BIANCO

112905.01

ROSONE PLAFONE D. 55 NERO

112905.02

ROSONE PLAFONE D. 55 LIGHT GREY

112905.23

ROSONE PLAFONE D. 55 DARK GREY

112905.24

ROSONE INCASSO DIAM. 40 BIANCO

112906.01

ROSONE INCASSO DIAM. 40 NERO

112906.02

ROSONE INCASSO DIAM. 40 LIGHT GREY

112906.23

	ROSONE INCASSO DIAM. 40 DARK GREY	112906.24
	ROSONE LINEARE 3 X L=620 BIANCO	112907.01
	ROSONE LINEARE 3 X L=620 NERO	112907.02
	ROSONE LINEARE 3 X L=620 LIGHT GREY	112907.23
	ROSONE LINEARE 3 X L=620 DARK GREY	112907.24
	ROSONE CIRCOLARE 3 X D. 200 BIANCO	112908.01
	ROSONE CIRCOLARE 3 X D. 200 NERO	112908.02
	ROSONE CIRCOLARE 3 X D. 200 LIGHT GREY	112908.23
	ROSONE CIRCOLARE 3 X D. 200 DARK GREY	112908.24