



Features

Use: Indoor
Type of installation: WALL, SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: OPAL
Colour: GOLD
Dimming: PUSH, DALI
Emergency: NO
H: 70mm
ø: 995mm
Made in: ITALY
Warranty: 5 years
Weight: 12,5kg

Tech data

Luminaire input power: 125W
Luminaire luminous flux: 11882lm
IP: 40
Insulation class: I
No. of driver per product: 5
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 101W
Source luminous flux: 15695lm
Colour temperature: 3000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[ROTO EVO: View more product info](#)

ROTO EVO

113135.22

novalux
ITALIAN LIGHTING DESIGN SINCE 1948

MOUNTING ACCESSORIES



ROTO EVO: KIT SOSPENSIONE L=3000 1PZ

113137.99



ROTO EVO: KIT PLAFONE/PARETE D.995

113139.99



ROSONE 5X1,5 TND 3000 ORO

109007.22



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 6/8/2025, 12:49:24