



Features

Use: Indoor
Optics: MICRO OPTICS
Beam: 40°
Colour: BLACK
Dimming: WITH ACCESSORY
Emergency: NO
L: 1272mm
A: 30mm
H: 24mm
Made in: ITALY
Warranty: 5 years
Weight: 0.4kg

Tech data

Luminaire input power: 40W
Luminaire luminous flux: 3596lm
IP: 40
Insulation class: III
Supply voltage: DC 700 MA
UGR: <19
SELV: No

Source

Light source: LED
Source power: 34W
Source luminous flux: 4144lm
Colour temperature: 2700K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[HERO MINI B: View more product info](#)

[CAOS: View more product info](#)

[CAOS B: View more product info](#)

[HERO MINI: View more product info](#)

