

## Features

Use: Indoor  
Type of installation: RECESSED INTO PLASTERBOARD  
Emission: DIRECT  
Optics: MICROPRISMATIZED  
Colour: WHITE  
Dimming: PUSH, DALI  
Emergency: WITH ACCESSORY  
L: 595mm  
A: 595mm  
H: 35mm  
Warranty: 3 years  
Weight: 3kg

## Tech data

Luminaire input power: 36W  
Luminaire luminous flux: 3892lm  
Luminous flux in emergency: 1h: 12% / 3h: 5  
IP: 40  
Insulation class: II  
Supply voltage: 900mA driver incluso  
UGR: <19 4H-8H S=0,25  
SELV: Si

## Source

Light source: LED  
Source power: 32W  
Colour temperature: 4000K  
CRI: >80  
LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

## MOUNTING ACCESSORIES

---




BACKLIT: KIT MOLLE INC.CART.600/1200

**113609.99**


## EMERGENCY ACCESSORIES

---



THE PANEL 2: EMER.INC.1H 10/54VDC

**1020A4.99**



THE PANEL 2: EMER.INC.3H 10/54VDC

**1020A5.99**