

Features

Use: Indoor

Type of installation: RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED

Emission: DIRECT

Optics: MICROPRISMATIZED

Colour: WHITE

Dimming: ON/OFF

Emergency: WITH ACCESSORY

L: 1195mm

A: 295mm

H: 30mm

Warranty: 3 years

Tech data

Luminaire input power: 38W

Luminaire luminous flux: 4503lm

Luminous flux in emergency: 1h: 12% / 3h: 5

IP: 40

Insulation class: II

No. of driver per product: 1

Supply voltage: 950mA driver included

UGR: <19

SELV: Si

Source

Light source: LED

Source power: 34W

Source luminous flux: 5757lm

Colour temperature: 4000K

CRI: >80

LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012




Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.



CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

MOUNTING ACCESSORIES

	BACKLIT: KIT MOLLE INC.CART.600/1200 MG	113620.99
	BACKLIT: BOX PER INST. SOSP.1200X300 BIA	113638.01
	BACKLIT: KIT ANTICADUTA	113639.99
	THE PANEL 2: KIT INST.INC.RAS.CART.1200	102029.99
	KIT ALIMENTAZIONE L1200 3P BIA	108919.01
	KIT ALIMENTAZIONE L3000 3P BIA	108920.01
	KIT ALIMENTAZIONE L1200 5P BIA	108921.01
	KIT ALIMENTAZIONE L3000 5P BIA	108922.01
	BACKLIT: BOX PER INST. PLAF. 1200X300 BI	113611.01

EMERGENCY ACCESSORIES

	THE PANEL 2: EMER.INC.1H 10/54VDC	1020A4.99
	THE PANEL 2: EMER.INC.3H 10/54VDC	1020A5.99