

Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: MICROPRISMATIZED
Colour: WHITE
Dimming: PUSH, DALI
Emergency: WITH ACCESSORY
L: 1195mm
A: 295mm
H: 30mm
Warranty: 3 years

Tech data

Luminaire input power: 38W
Luminaire luminous flux: 4503lm
Luminous flux in emergency: 1h: 12% / 3h: 5
IP: 40
Insulation class: II
No. of driver per product: 1
Supply voltage: 950mA driver included
UGR: <19
SELV: Si

Source

Light source: LED
Source power: 34W
Source luminous flux: 5757lm
Colour temperature: 4000K
CRI: >80
LED lifespan: 50000h L80 B20

Compliance




CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards



Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

MOUNTING ACCESSORIES

	BACKLIT: KIT MOLLE INC.CART.600/1200 MG	113620.99
	BACKLIT: BOX PER INST. SOSP.1200X300 BIA	113638.01
	BACKLIT: KIT ANTICADUTA	113639.99
	THE PANEL 2: KIT INST.INC.RAS.CART.1200	102029.99
	KIT ALIMENTAZIONE L1200 3P BIA	108919.01
	KIT ALIMENTAZIONE L3000 3P BIA	108920.01
	KIT ALIMENTAZIONE L1200 5P BIA	108921.01
	KIT ALIMENTAZIONE L3000 5P BIA	108922.01
	BACKLIT: BOX PER INST. PLAF. 1200X300 BI	113611.01

EMERGENCY ACCESSORIES

	THE PANEL 2: EMER.INC.1H 10/54VDC	1020A4.99
	THE PANEL 2: EMER.INC.3H 10/54VDC	1020A5.99