

Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: MICRO OPTICS
Beam: 40°
Colour: BLACK
Dimming: WITH ACCESSORY
Emergency: WITH ACCESSORY
L: 116mm
A: 22mm
H: 58mm
Warranty: 5 years
Weight: 0.19kg

Tech data

Luminaire luminouse flux: 622lm
Luminous flux in emergency: 1h: 56% / 3h: 22
IP: 40
Insulation class: III
Supply voltage: DC 200 mA
SELV: Si

Source

Light source: LED
Source power: 8W
Colour temperature: 3000K
CRI: >90
LED lifespan: 30000h L70 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 1 Certified fixture in RISK GROUP 1 (Low Risk)-The fixture does not pose a hazard due to normal behavioral limitations on exposure - in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

[View more product info](#)

ELECTRICAL ACCESSORIES



ALIM. LED 8W 200MA/30-42V

101345.99


DIMMABLE ACCESSORIES



ALIM. LED 8W 200MA/9-42V DALI/PUSH


101346.99

EMERGENCY ACCESSORIES



KIT EMERGENZA 1H 10V-54V

18004.99



KIT EMERGENZA 3H 10V-54V

18005.99