



Features

Use: Indoor
Type of installation: SUSPENDED
Emission: DIRECT/INDIRECT
Optics: OPAL
Colour: WHITE
Dimming: DALI2, PUSH
Emergency: NO
L: 1314mm
A: 1138mm
H: 72mm
Made in: ITALY
Warranty: 5 years
Weight: 10.2kg

Tech data

Luminaire input power: 110W
Luminaire luminous flux: 9560lm
Direct luminous flux: 5582lm
Indirect luminous flux: 3978lm
IP: 40
Insulation class: I
No. of driver per product: 3
Supply voltage: 220-240V 50/60Hz
UGR: <19
SELV: Si

Source

Light source: LED
Source power: 105W
Source luminous flux: 10152lm
Colour temperature: 2700K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L90 B10


Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

[SIX B: View more product info](#)



MOUNTING ACCESSORIES

	ROSONE 3X1,5 TND 3000 BIA	109005.01
	ROSONE 3X1,5 QDR 3000 BIA	109006.01
	ROSONE 5X1,5 TND 3000 BIA	109007.01
	ROSONE 5X1,5 QDR 3000 BIA	109008.01