

SIX B

114507.21

novalux
ITALIAN LIGHTING DESIGN SINCE 1948




Features

Use: Indoor
Type of installation: SUSPENDED
Emission: DIRECT/INDIRECT
Optics: OPAL
Colour: CAPPUCCINO
Dimming: DALI2, PUSH
Emergency: NO
L: 1314mm
A: 1138mm
H: 72mm
Made in: ITALY
Warranty: 5 years
Weight: 10.2kg

Tech data

Luminaire input power: 110W
Luminaire luminous flux: 9560lm
Direct luminous flux: 5582lm
Indirect luminous flux: 3978lm
IP: 40
Insulation class: I
No. of driver per product: 3
Supply voltage: 220-240V 50/60Hz
UGR: <19
SELV: Si



Source

Light source: LED
Source power: 105W
Source luminous flux: 10152lm
Colour temperature: 2700K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

[SIX B: View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 29/5/2026, 16:24:15

MOUNTING ACCESSORIES



ROSONE 3X1,5 TND 3000 CAPP

109005.21



ROSONE 3X1,5 QDR 3000 CAPP

109006.21



ROSONE 5X1,5 TND 3000 CAPP

109007.21



ROSONE 5X1,5 QDR 3000 CAPP

109008.21