


# SIX B

114510.20

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



## Features

Use: Indoor  
Type of installation: SUSPENDED  
Emission: DIRECT/INDIRECT  
Optics: MICRO OPTICS  
Colour: CAFFE  
Dimming: DALI2, PUSH  
Emergency: NO  
L: 1314mm  
A: 1138mm  
H: 72mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 10.2kg

## Tech data

Luminaire input power: 70W  
Luminaire luminous flux: 6540lm  
Direct luminous flux: 2562lm  
Indirect luminous flux: 3978lm  
IP: 40  
Insulation class: I  
No. of driver per product: 2  
Supply voltage: 220-240V 50/60Hz  
UGR: <19  
SELV: Si

## Source

Light source: LED  
Source power: 61W  
Source luminous flux: 2850lm  
Colour temperature: 2700K  
CRI: >90  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L90 B10

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

[SIX B: View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 29/5/2026, 16:24:15

## MOUNTING ACCESSORIES

---



ROSONE 3X1,5 TND 3000 CAF

**109005.20**

---



ROSONE 3X1,5 QDR 3000 CAF

**109006.20**

---



ROSONE 5X1,5 TND 3000 CAF

**109007.20**

---



ROSONE 5X1,5 QDR 3000 CAF

**109008.20**