

# HERO PLUS

114643.20 + 108933.99

HERO+: EM 40W 2.7K 1680 CAF + HERO+: DIFF. OPALE ALTA TRASMIT PER 1680



**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



## Features

Use: Indoor

Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK

Emission: DIRECT

Optics: HIGH-TRANSMITTANCE OPAL DIFFUSER

Colour: CAFE

Dimming: ON/OFF

Emergency: Autonomy 1h/Recharge time 12h

L: 1680mm

A: 53mm

H: 69mm

Made in: ITALY

Warranty: 5 years except battery

Weight: 5.2kg

## Tech data

Luminaire input power: 44W

Luminaire luminous flux: 4771lm

Luminous flux in emergency: 10%

IP: 40

Insulation class: I

No. of driver per product: 1

Supply voltage: 220-240V 50/60Hz

SELV: Si

## Source

Light source: LED

Source power: 40W

Source luminous flux: 6228lm

Colour temperature: 2700K

CRI: >90

Colour tolerance: 3 Step MacAdam

LED lifespan: 50000h L90 B10

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012, CEI EN 60598-2-22:2023

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

## Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2011).

[HERO PLUS: View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: [info@novalux.it](mailto:info@novalux.it) · VAT number 00536541204 · [novalux.com](http://novalux.com)  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 9/6/2026, 17:10:01

# HERO PLUS

114643.20 + 108933.99

HERO+: EM 40W 2.7K 1680 CAF + HERO+: DIFF. OPALE ALTA TRASMIT PER 1680



**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



## Features

Use: Indoor  
Optics: HIGH-TRANSMITTANCE OPAL DIFFUSER  
L: 1680mm  
A: 48mm  
H: 6mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 0.4kg

## Tech data

IP: 40  
SELV: No

## Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2011).



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: [info@novalux.it](mailto:info@novalux.it) · VAT number 00536541204 · [novalux.com](http://novalux.com)  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 9/6/2026, 17:10:01

# HERO PLUS

114643.20 + 108933.99

HERO+: EM 40W 2.7K 1680 CAF + HERO+: DIFF. OPALE ALTA TRASMIT PER 1680

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948

## COMPLETION ACCESSORIES

|                                                                                     |                                        |           |
|-------------------------------------------------------------------------------------|----------------------------------------|-----------|
|    | HERO: TESTATA OPALE PER SCHERMO TL 2PZ | 108930.99 |
|    | HERO+: KIT DI GIUNZIONE PROFILI 1PZ    | 108940.99 |
|    | HERO: COPPIA TESTATE CAF               | 108684.20 |
|    | HERO+: MOD.CIECO 280 CAF               | 114685.20 |
|    | HERO+: MOD.CIECO 1120 CAF              | 114686.20 |
|  | HERO+: MOD.CIECO 1400 CAF              | 114687.20 |
|  | HERO+: MOD.CIECO 1680 CAF              | 114688.20 |
|   | HERO+: MOD.CIECO ANG. SX DX 150 CAF    | 114689.20 |

## MOUNTING ACCESSORIES

|                                                                                     |                                        |           |
|-------------------------------------------------------------------------------------|----------------------------------------|-----------|
|  | HERO: SOSP.L3000 1PZ TESTA W.G.ALTO    | 1086A1.99 |
|  | HERO+: SOSP L.3M REGOLA. DAL BASSO 1PZ | 114694.99 |



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: [info@novalux.it](mailto:info@novalux.it) · VAT number 00536541204 · [novalux.com](http://novalux.com)  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 9/6/2026, 17:10:01

# HERO PLUS

114643.20 + 108933.99

HERO+: EM 40W 2.7K 1680 CAF + HERO+: DIFF. OPALE ALTA TRASMIT PER 1680

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948

|                                                                                     |                                 |           |
|-------------------------------------------------------------------------------------|---------------------------------|-----------|
|    | HERO: STAFFA PARETE "L" BIA     | 108687.01 |
|    | HERO: STAFFA PARETE "L" NE      | 108687.02 |
|    | HERO: STAFFA PARETE "L" CAF     | 108687.20 |
|    | HERO: STAFFA PARETE "L" CAP     | 108687.21 |
|    | HERO: KIT INCASSO LED (1X)      | 108688.99 |
|   | HERO: SPESS. CARTONG. 10MM 2PZ. | 108689.99 |
|  | KIT ALIMENTAZIONE L3000 3P BIA  | 108920.01 |
|  | KIT ALIMENTAZIONE L3000 3P NE   | 108920.02 |
|  | KIT ALIMENTAZIONE L3000 3P CAF  | 108920.20 |
|  | KIT ALIMENTAZIONE L3000 3P CAP  | 108920.21 |



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: [info@novalux.it](mailto:info@novalux.it) · VAT number 00536541204 · [novalux.com](http://novalux.com)  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 9/6/2026, 17:10:01