

# HERO PLUS

114650.21 + 108944.99

HERO+: ANG.SX 27W 3K 594 CAP + HERO+: DIFFUSORE OPALE PER ANGOLO 594

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



## Features

Use: Indoor  
Type of installation: WALL, RECESSED INTO PLASTERBOARD, SUSPENDED, CEILING MOUNTED, TRACK  
Emission: DIRECT  
Optics: OPAL  
Colour: CAPPUCCINO  
Dimming: ON/OFF  
Emergency: NO  
L: 594x594mm  
A: 53mm  
H: 69mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 2.1kg

## Tech data

Luminaire input power: 30W  
Luminaire luminous flux: 2680lm  
IP: 40  
Insulation class: I  
No. of driver per product: 1  
Supply voltage: 220-240V 50/60Hz  
SELV: Si

## Source

Light source: LED  
Source power: 27W  
Source luminous flux: 4436lm  
Colour temperature: 3000K  
CRI: >90  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L90 B10

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

## Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2011).

[HERO PLUS: View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 29/5/2026, 17:03:18

# HERO PLUS

114650.21 + 108944.99

HERO+: ANG.SX 27W 3K 594 CAP + HERO+: DIFFUSORE OPALE PER ANGOLO 594

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



## Features

Use: Indoor  
Optics: OPAL  
L: 594x594mm  
A: 48mm  
H: 6mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 0.2kg

## Tech data

IP: 40  
SELV: No

## Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2011).



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 29/5/2026, 17:03:18








# HERO PLUS

114650.21 + 108944.99

HERO+: ANG.SX 27W 3K 594 CAP + HERO+: DIFFUSORE OPALE PER ANGOLO 594

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948

## COMPLETION ACCESSORIES

|   |                                     |           |
|---|-------------------------------------|-----------|
|    | HERO+: KIT DI GIUNZIONE PROFILI 1PZ | 108940.99 |
|    | HERO: COPPIA TESTATE CAP            | 108684.21 |
|    | HERO+: MOD.CIECO 280 CAP            | 114685.21 |
|    | HERO+: MOD.CIECO 1120 CAP           | 114686.21 |
|    | HERO+: MOD.CIECO 1400 CAP           | 114687.21 |
|  | HERO+: MOD.CIECO 1680 CAP           | 114688.21 |
|  | HERO+: MOD.CIECO ANG. SX DX 150 CAP | 114689.21 |

## MOUNTING ACCESSORIES

|   |  |           |
|---|--|-----------|
|  | HERO: SOSPL.3000 1PZ TESTA W.G.ALTO    | 1086A1.99 |
|  | HERO+: SOSP L.3M REGOLA. DAL BASSO 1PZ | 114694.99 |
|  | ALL-TRACK EVO: COPPIA ADATT. 3P BI     | 106757.01 |



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 29/5/2026, 17:03:18

# HERO PLUS

114650.21 + 108944.99

HERO+: ANG.SX 27W 3K 594 CAP + HERO+: DIFFUSORE OPALE PER ANGOLO 594

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948

|   |   |                  |
|---|---|------------------|
|    | ALL-TRACK EVO: COPPIA ADATT. 3P NE      | <b>106757.02</b> |
|    | ALL-TRACK EVO: COPPIA ADATT. 3P+DALI BI | <b>106758.01</b> |
|    | ALL-TRACK EVO: COPPIA ADATT. 3P+DALI NE | <b>106758.02</b> |
|    | HERO: STAFFA PARETE "L" BIA             | <b>108687.01</b> |
|    | HERO: STAFFA PARETE "L" NE              | <b>108687.02</b> |
|   | HERO: STAFFA PARETE "L" CAF             | <b>108687.20</b> |
|  | HERO: STAFFA PARETE "L" CAP             | <b>108687.21</b> |
|  | HERO: KIT INCASSO LED (1X)              | <b>108688.99</b> |
|  | HERO: SPESS. CARTONG. 10MM 2PZ.         | <b>108689.99</b> |
|  | KIT ALIMENTAZIONE L3000 3P BIA          | <b>108920.01</b> |
|  | KIT ALIMENTAZIONE L3000 3P NE           | <b>108920.02</b> |
|  | KIT ALIMENTAZIONE L3000 3P CAF          | <b>108920.20</b> |



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 29/5/2026, 17:03:18

# HERO PLUS

114650.21 + 108944.99

HERO+: ANG.SX 27W 3K 594 CAP + HERO+: DIFFUSORE OPALE PER ANGOLO 594

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



KIT ALIMENTAZIONE L3000 3P CAP

**108920.21**



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 29/5/2026, 17:03:18