



HERO PLUS B

114719.01 + 108927.99

HERO+B: 99W 4K 2240 BIA + HERO: DIFF. OPALE TL PER 2240



novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Features

Use: Indoor
Type of installation: SUSPENDED
Emission: DIRECT/INDIRECT
Optics: OPAL FULL LIGHT
Colour: WHITE
Dimming: ON/OFF
Emergency: NO
L: 2240mm
A: 53mm
H: 92mm
Made in: ITALY
Warranty: 5 years
Weight: 8kg

Tech data

Luminaire input power: 109W
Luminaire luminous flux: 6788lm
Indirect luminous flux: 5695lm
IP: 40
Insulation class: I
No. of driver per product: 2
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 99W
Source luminous flux: 9208lm
Colour temperature: 4000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

[HERO PLUS B: View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 9/6/2026, 17:16:15

HERO PLUS B

114719.01 + 108927.99

HERO+B: 99W 4K 2240 BIA + HERO: DIFF. OPALE TL PER 2240



novalux
ITALIAN LIGHTING DESIGN SINCE 1948




Features

Optics: OPAL FULL LIGHT
L: 2240mm
A: 52.5mm
H: 15mm
Made in: ITALY
Warranty: 5 years
Weight: 0.13kg

Tech data

IP: 40
SELV: No



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 9/6/2026, 17:16:15


HERO PLUS B

114719.01 + 108927.99

HERO+B: 99W 4K 2240 BIA + HERO: DIFF. OPALE TL PER 2240

novalux
ITALIAN LIGHTING DESIGN SINCE 1948

COMPLETION ACCESSORIES

	HERO: TESTATA OPALE PER SCHERMO TL 2PZ	108930.99
	HERO+: KIT DI GIUNZIONE PROFILI 1PZ	108940.99
	HERO B: COPPIA TESTATE BIA	1087B1.01
	HERO+B: MOD.CIECO 280 BIA	114785.01
	HERO+B: MOD.CIECO 1120 BIA	114786.01
	HERO+B: MOD.CIECO 1400 BIA	114787.01
	HERO+B: MOD.CIECO 1680 BIA	114788.01
	HERO+B: MOD.CIECO ANG. SX DX 150 BIA	114789.01

MOUNTING ACCESSORIES

	KIT SOSPENSIONE HERO+B/MINI B L.1.2M 2PZ	114794.99
	KIT SOSPENSIONE HERO+B/MINI B L. 3M 2PZ	114795.99



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 9/6/2026, 17:16:15

HERO PLUS B

114719.01 + 108927.99

HERO+B: 99W 4K 2240 BIA + HERO: DIFF. OPALE TL PER 2240

	KIT SOSPENSIONE HERO+B/MINI B L.1.2M 3PZ	114796.99
	KIT SOSPENSIONE HERO+B/MINI B L. 3M 3PZ	114797.99
	KIT ALIMENTAZIONE L3000 3P BIA	108920.01
	KIT ALIMENTAZIONE L3000 5P BIA	108922.01
EMERGENCY ACCESSORIES		
	HERO+: KIT 2 CAVI 1X1.5 EMERGE. L.2800	108943.99