# HERO PLUS B

**114738.01 + 108903.99**

HERO+B: 73W 4K 1680 DALI/PUSH BIA + HERO: DIFF. OPALE PER 1680






## Features

Use: Indoor
Type of installation: SUSPENDED
Emission: DIRECT/INDIRECT
Optics: OPAL
Colour: WHITE
Dimming: DALI2, PUSH
Emergency: NO
L: 1680mm
A: 53mm
H: 92mm
Made in: ITALY
Warranty: 5 years
Weight: 6kg

## Tech data

Luminaire input power: 80,5W
Luminaire luminouse flux: 4171lm
Indirect luminous flux: 4068lm
IP: 40
Insulation class: I
No. of driver per product: 2
Supply voltage: 220-240V 50/60Hz
SELV: Sì

## Source

Light source: LED
Source power: 73W
Source luminous flux: 11090lm
Colour temperature: 4000K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L90 B10

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

## Standards

Photobiological risk: RISK GROUP 0Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

HERO PLUS B: View more product info

Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV Gmbh



**This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.**
**Last update: 9/6/2026, 17:18:27**

# HERO PLUS B

**114738.01 + 108903.99**

HERO+B: 73W 4K 1680 DALI/PUSH BIA + HERO: DIFF. OPALE PER 1680



## Features

Optics: OPAL
L: 1680mm
A: 48mm
H: 6mm
Made in: ITALY
Warranty: 5 years
Weight: 0.4kg

## Tech data

IP: 40
SELV: No



**This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.**


**Last update: 9/6/2026, 17:18:27**

# HERO PLUS B

**114738.01 + 108903.99**

HERO+B: 73W 4K 1680 DALI/PUSH BIA + HERO: DIFF. OPALE PER 1680

## COMPLETION ACCESSORIES

| | | |
|---|---|---|
| | HERO: TESTATA OPALE PER SCHERMO TL 2PZ | **108930.99** |
| | HERO+: KIT DI GIUNZIONE PROFILI 1PZ | **108940.99** |
| | HERO B: COPPIA TESTATE BIA | **1087B1.01** |
|  | HERO+B: MOD.CIECO 280 BIA | **114785.01** |
|  | HERO+B: MOD.CIECO 1120 BIA | **114786.01** |
|  | HERO+B: MOD.CIECO 1400 BIA | **114787.01** |
|  | HERO+B: MOD.CIECO 1680 BIA | **114788.01** |
|  | HERO+B: MOD.CIECO ANG. SX DX 150 BIA | **114789.01** |

## MOUNTING ACCESSORIES

| | | |
|---|---|---|
| | KIT SOSPENSIONE HERO+B/MINI B L.1.2M 2PZ | **114794.99** |
| | KIT SOSPENSIONE HERO+B/MINI B L. 3M 2PZ | **114795.99** |

Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV Gmbh



**This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.**
**Last update: 9/6/2026, 17:18:27**

# HERO PLUS B

**114738.01 + 108903.99**

HERO+B: 73W 4K 1680 DALI/PUSH BIA + HERO: DIFF. OPALE PER 1680

| | | |
|---|---|---|
|  | KIT SOSPENSIONE HERO+B/MINI B L.1.2M 3PZ | **114796.99** |
| | KIT SOSPENSIONE HERO+B/MINI B L. 3M 3PZ | **114797.99** |
| | KIT ALIMENTAZIONE L3000 3P BIA | **108920.01** |
| | KIT ALIMENTAZIONE L3000 5P BIA | **108922.01** |

**EMERGENCY ACCESSORIES**

| | | |
|---|---|---|
| | HERO+: KIT 2 CAVI 1X1.5 EMERGE. L.1960 | **108942.99** |

Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV Gmbh



**This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.**
**Last update: 9/6/2026, 17:18:27**