

# HERO PLUS B

114741.20 + 108928.99

HERO+B: 113W 4K 2520 DALI/PUSH CAF + HERO: DIFF. OPALE TL PER 2520



**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



## Features

Use: Indoor  
Type of installation: SUSPENDED  
Emission: DIRECT/INDIRECT  
Optics: OPAL FULL LIGHT  
Colour: CAFFE  
Dimming: DALI2, PUSH  
Emergency: NO  
L: 2520mm  
A: 53mm  
H: 92mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 9kg

## Tech data

Luminaire input power: 124,5W  
Luminaire luminous flux: 7636lm  
Indirect luminous flux: 6509lm  
IP: 40  
Insulation class: I  
No. of driver per product: 2  
Supply voltage: 220-240V 50/60Hz  
SELV: Si

## Source

Light source: LED  
Source power: 113W  
Source luminous flux: 11090lm  
Colour temperature: 4000K  
CRI: >90  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L90 B10

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

[HERO PLUS B: View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: [info@novalux.it](mailto:info@novalux.it) · VAT number 00536541204 · [novalux.com](http://novalux.com)  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 9/6/2026, 17:18:51

# HERO PLUS B

114741.20 + 108928.99

HERO+B: 113W 4K 2520 DALI/PUSH CAF + HERO: DIFF. OPALE TL PER 2520



**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



## Features

Optics: OPAL FULL LIGHT  
L: 2520mm  
A: 52.5mm  
H: 15mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 0.13kg

## Tech data

IP: 40  
SELV: No



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: [info@novalux.it](mailto:info@novalux.it) · VAT number 00536541204 · [novalux.com](http://novalux.com)  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 9/6/2026, 17:18:51

# HERO PLUS B

114741.20 + 108928.99

HERO+B: 113W 4K 2520 DALI/PUSH CAF + HERO: DIFF. OPALE TL PER 2520

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948

## COMPLETION ACCESSORIES

|                                                                                    |                                        |           |
|------------------------------------------------------------------------------------|----------------------------------------|-----------|
|   | HERO: TESTATA OPALE PER SCHERMO TL 2PZ | 108930.99 |
|   | HERO+: KIT DI GIUNZIONE PROFILI 1PZ    | 108940.99 |
|   | HERO B: COPPIA TESTATE CAF             | 1087B1.20 |
|    | HERO+B: MOD.CIECO 280 CAF              | 114785.20 |
|    | HERO+B: MOD.CIECO 1120 CAF             | 114786.20 |
|  | HERO+B: MOD.CIECO 1400 CAF             | 114787.20 |
|  | HERO+B: MOD.CIECO 1680 CAF             | 114788.20 |
|  | HERO+B: MOD.CIECO ANG. SX DX 150 CAF   | 114789.20 |

## MOUNTING ACCESSORIES

|                                                                                     |                                          |           |
|-------------------------------------------------------------------------------------|------------------------------------------|-----------|
|  | KIT SOSPENSIONE HERO+B/MINI B L.1.2M 2PZ | 114794.99 |
|  | KIT SOSPENSIONE HERO+B/MINI B L. 3M 2PZ  | 114795.99 |



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: [info@novalux.it](mailto:info@novalux.it) · VAT number 00536541204 · [novalux.com](http://novalux.com)  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 9/6/2026, 17:18:51

# HERO PLUS B

**114741.20 + 108928.99**

HERO+B: 113W 4K 2520 DALI/PUSH CAF + HERO: DIFF. OPALE TL PER 2520

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



KIT SOSPENSIONE HERO+B/MINI B L.1.2M 3PZ

**114796.99**



KIT SOSPENSIONE HERO+B/MINI B L. 3M 3PZ

**114797.99**



KIT ALIMENTAZIONE L3000 3P CAF

**108920.20**



KIT ALIMENTAZIONE L3000 5P CAF

**108922.20**

## EMERGENCY ACCESSORIES



HERO+: KIT 2 CAVI 1X1.5 EMERGE. L.2800

**108943.99**



Novalux S.r.l. via Marzabotto, 2 40050 Fano di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: [info@novalux.it](mailto:info@novalux.it) · VAT number 00536541204 · [novalux.com](http://novalux.com)  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 9/6/2026, 17:18:51