

HERO PLUS B

114743.20 + 108933.99

HERO+B: EM 73W 2.7K 1680 CAF + HERO+: DIFF. OPALE ALTA TRASMIT PER 1680

novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Features

Use: Indoor
Type of installation: SUSPENDED
Emission: DIRECT/INDIRECT
Optics: HIGH-TRANSMITTANCE OPAL DIFFUSER
Colour: CAFFE
Dimming: ON/OFF
Emergency: Autonomy 1h/Recharge time 12h
L: 1680mm
A: 53mm
H: 92mm
Made in: ITALY
Warranty: 5 years except battery
Weight: 7kg

Tech data

Luminaire input power: 80,5W
Luminaire luminous flux: 4771lm
Indirect luminous flux: 3668lm
Luminous flux in emergency: 10%
IP: 40
Insulation class: I
No. of driver per product: 2
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 73W
Source luminous flux: 6228lm
Colour temperature: 2700K
CRI: >90
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-22:2023

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2011).

[HERO PLUS B: View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 29/5/2026, 17:10:12

HERO PLUS B

114743.20 + 108933.99

HERO+B: EM 73W 2.7K 1680 CAF + HERO+: DIFF. OPALE ALTA TRASMIT PER 1680

novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Features

Use: Indoor
Optics: HIGH-TRANSMITTANCE OPAL DIFFUSER
L: 1680mm
A: 48mm
H: 6mm
Made in: ITALY
Warranty: 5 years
Weight: 0.4kg

Tech data

IP: 40
SELV: No

Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2011).



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 29/5/2026, 17:10:12

HERO PLUS B

114743.20 + 108933.99

HERO+B: EM 73W 2.7K 1680 CAF + HERO+: DIFF. OPALE ALTA TRASMIT PER 1680

novalux
ITALIAN LIGHTING DESIGN SINCE 1948

COMPLETION ACCESSORIES

| | | |
|---|--|-----------|
|  | HERO: TESTATA OPALE PER SCHERMO TL 2PZ | 108930.99 |
|  | HERO+: KIT DI GIUNZIONE PROFILI 1PZ | 108940.99 |
|  | HERO B: COPPIA TESTATE CAF | 1087B1.20 |
|  | HERO+B: MOD.CIECO 280 CAF | 114785.20 |
|  | HERO+B: MOD.CIECO 1120 CAF | 114786.20 |
|  | HERO+B: MOD.CIECO 1400 CAF | 114787.20 |
|  | HERO+B: MOD.CIECO 1680 CAF | 114788.20 |
|  | HERO+B: MOD.CIECO ANG. SX DX 150 CAF | 114789.20 |

MOUNTING ACCESSORIES

| | | |
|---|---|-----------|
|  | KIT SOSPENSIONE HERO+B/MINI B L. 1.2M 2PZ | 114794.99 |
|  | KIT SOSPENSIONE HERO+B/MINI B L. 3M 2PZ | 114795.99 |



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 29/5/2026, 17:10:12

HERO PLUS B

114743.20 + 108933.99

HERO+B: EM 73W 2.7K 1680 CAF + HERO+: DIFF. OPALE ALTA TRASMIT PER 1680

novalux
ITALIAN LIGHTING DESIGN SINCE 1948



KIT SOSPENSIONE HERO+B/MINI B L.1.2M 3PZ

114796.99



KIT SOSPENSIONE HERO+B/MINI B L.3M 3PZ

114797.99



KIT ALIMENTAZIONE L3000 3P CAF

108920.20



KIT ALIMENTAZIONE L3000 5P CAF

108922.20

EMERGENCY ACCESSORIES



HERO+: KIT 2 CAVI 1X1.5 EMERGE. L.1400

108941.99



HERO+: KIT 2 CAVI 1X1.5 EMERGE. L.1960

108942.99



HERO+: KIT 2 CAVI 1X1.5 EMERGE. L.2800

108943.99



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 29/5/2026, 17:10:12