

# HERO PLUS C

114824.01 + 108933.99

HERO+C: EM 40W 4K 1680 DALI BIA + HERO+: DIFF. OPALE ALTA TRASMIT PER 1680



**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



## Features

Use: Indoor  
Type of installation: RECESSED INTO PLASTERBOARD  
Emission: DIRECT  
Optics: HIGH-TRANSMITTANCE OPAL DIFFUSER  
Colour: WHITE  
Dimming: DALI2, PUSH  
Emergency: Autonomy 1h/Recharge time 12h  
L: 1680mm  
A: 53mm  
H: 69mm  
Made in: ITALY  
Warranty: 5 years except battery  
Weight: 5.2kg

## Tech data

Luminaire input power: 44W  
Luminaire luminous flux: 5290lm  
Luminous flux in emergency: 10%  
IP: 40  
Insulation class: I  
No. of driver per product: 1  
Supply voltage: 220-240V 50/60Hz  
SELV: Si

## Source

Light source: LED  
Source power: 40W  
Source luminous flux: 6906lm  
Colour temperature: 4000K  
CRI: >90  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L90 B10

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012, CEI EN 60598-2-22:2023

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

## Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2011).

[HERO PLUS C: View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 29/5/2026, 17:12:31

# HERO PLUS C

114824.01 + 108933.99

HERO+C: EM 40W 4K 1680 DALI BIA + HERO+: DIFF. OPALE ALTA TRASMIT PER 1680

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948



## Features

Use: Indoor  
Optics: HIGH-TRANSMITTANCE OPAL DIFFUSER  
L: 1680mm  
A: 48mm  
H: 6mm  
Made in: ITALY  
Warranty: 5 years  
Weight: 0.4kg

## Tech data

IP: 40  
SELV: No

## Average luminance

Average luminance limits for DSE workstation 65°(in accordance to EN 12464-1:2011).



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 29/5/2026, 17:12:31

# HERO PLUS C

114824.01 + 108933.99

HERO+C: EM 40W 4K 1680 DALI BIA + HERO+: DIFF. OPALE ALTA TRASMIT PER 1680

**novalux**  
ITALIAN LIGHTING DESIGN SINCE 1948

## COMPLETION ACCESSORIES

	HERO: TESTATA OPALE PER SCHERMO TL 2PZ	<b>108930.99</b>
	HERO C: COPPIA TESTATE BIA	<b>108860.01</b>
	HERO+C: MOD.CIECO 280 BIA	<b>114861.01</b>
	HERO+C: MOD.CIECO 1120 BIA	<b>114862.01</b>
	HERO+C: MOD.CIECO 1400 BIA	<b>114863.01</b>
	HERO+C: MOD.CIECO 1680 BIA	<b>114864.01</b>
	HERO+C: MOD.CIECO ANG.SX DX 150 BI	<b>114865.01</b>



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy  
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com  
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.  
Last update: 29/5/2026, 17:12:31