



## Features

Use: Indoor  
Type of installation: WALL, SUSPENDED, CEILING MOUNTED  
Emission: DIRECT/INDIRECT  
Optics: MICROPRISMATIZED  
Colour: WHITE  
Dimming: ON/OFF  
Emergency: NO  
H: 65mm  
ø: 450mm  
Warranty: 5 years  
Weight: 3.5kg

## Tech data

Luminaire input power: 36W  
Luminaire luminous flux: (3K D) 3422lm (3K D/l) 2915/324lm | (4K D) 3617lm (4K D/l) 3082/342lm  
IP: 40  
Insulation class: I  
No. of driver per product: 1  
Supply voltage: 220-240V 50/60Hz  
SELV: Si

## Source

Light source: LED  
Source power: 32W  
Colour temperature: 3000K/4000K  
CRI: >90  
LED lifespan: 50000h L90 B10

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

[ROB: View more product info](#)

## MOUNTING ACCESSORIES



ROB: KIT SOSPENSIONI 4PZ D450/600

**115005.99**



ROSONE 3X1,5 TND 3000 BIA

**109005.01**



ROSONE 3X1,5 TND 3000 NE

**109005.02**



ROSONE 5X1,5 TND 3000 BIA

**109007.01**



ROSONE 5X1,5 TND 3000 NE

**109007.02**