



Features

Use: Indoor
Type of installation: WALL, SUSPENDED, CEILING MOUNTED
Emission: DIRECT/INDIRECT
Optics: MICROPRISMATIZED
Colour: WHITE
Dimming: DALI2, PUSH
Emergency: NO
H: 65mm
ø: 600mm
Warranty: 5 years
Weight: 6kg

Tech data

Luminaire input power: 68W
Luminaire luminous flux: (3K D) 6699lm (3K D/l) 5865/510lm | (4K D) 7095lm (4K D/l) 6212/540lm
IP: 40
Insulation class: I
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 62W
Colour temperature: 3000K/4000K
CRI: >90
LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

[ROB: View more product info](#)

MOUNTING ACCESSORIES



ROB: KIT SOSPENSIONI 4PZ D450/600

115005.99



ROSONE 3X1,5 TND 3000 BIA

109005.01



ROSONE 3X1,5 TND 3000 NE

109005.02



ROSONE 5X1,5 TND 3000 BIA

109007.01



ROSONE 5X1,5 TND 3000 NE

109007.02