

LA STAGNA 3.0

115203.03

novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Features

Use: Indoor, Outdoor
Type of installation: SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: OPAL
Colour: GREY
Dimming: ON/OFF
Emergency: 1 h
L: 1200mm
A: 80mm
H: 70mm
Warranty: 5 years
Weight: 1.8kg

Tech data

Luminaire input power: 26/32/39/46W
Luminaire luminous flux: 4078/5020/5848/6789lm
Luminous flux in emergency: 13%
IP: 65
Insulation class: I
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
IK: 7
SELV: No

Source

Light source: LED
Source power: 23/29/36/42W
Colour temperature: 4000K
CRI: >80
LED lifespan: 50000h L70 B50

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[LA STAGNA 3.0: View more product info](#)



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 29/5/2026, 16:26:40

LA STAGNA 3.0

115203.03

novalux
ITALIAN LIGHTING DESIGN SINCE 1948

MOUNTING ACCESSORIES



HERO+: SOSP L.3M REGOLA. DAL BASSO 1PZ

114694.99



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · VAT number 00536541204 · novalux.com
Company subject to the management and coordination by SLV GmbH

This technical data sheet is owned by Novalux S.r.l., all rights reserved. Novalux S.r.l. reserves the right to make changes without prior notice.
Last update: 29/5/2026, 16:26:40