



Features

Use: Indoor, Outdoor
Type of installation: WALL, CEILING MOUNTED
Emission: DIRECT
Optics: OPAL
Colour: WHITE
Dimming: ON/OFF
Emergency: WITH ACCESSORY
H: 50mm
ø: 300mm
Warranty: 5 years
Weight: 0.5kg

Tech data

Luminaire input power: 12/15/18W
Luminous flux in emergency: 8/6/5%
IP: 65
Insulation class: I
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
IK: 8
SELV: No

Source

Light source: LED
Source power: 11/14/16W
Colour temperature: 3000K/4000K/6500K
CRI: >80
LED lifespan: 50000h L80 B20

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[HULK: View more product info](#)

ELECTRICAL ACCESSORIES



HULK: SENSORE LUM./PRES. MW

115403.99

EMERGENCY ACCESSORIES



HULK: KIT EMERGENZA 1H

115402.99