

## Features

Use: Indoor  
Type of installation: SUSPENDED, CEILING MOUNTED  
Emission: DIRECT  
Optics: MICROPRISMATIZED  
Colour: WHITE  
Dimming: ON/OFF  
Emergency: NO  
L: 1440mm  
A: 46mm  
H: 70mm  
Warranty: 5 years  
Weight: 3.5kg

## Tech data

Luminaire input power: 31W  
Luminaire luminous flux: (3K) 3199lm / (4K) 3290lm  
IP: 40  
Insulation class: I  
No. of driver per product: 1  
Supply voltage: 220-240V 50/60Hz  
SELV: Si

## Source

Light source: LED  
Source power: 28W  
Source luminous flux: 5190lm  
Colour temperature: 3000K/4000K  
CRI: >80  
Colour tolerance: 3 Step MacAdam  
LED lifespan: 50000h L90 B10

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

[LYNO: View more product info](#)



## COMPLETION ACCESSORIES

---



LYNO: COPPIA TESTATE BIA

**115803.01**

---



LYNO: COPPIA STAFFE FISSAGGIO PLAFONE

**115804.99**


---



LYNO: COPPIA KIT SOSP. CAVO L 3M

**115805.99**

---



LYNO: STAFFA DI GIUNZIONE

**115806.99**

---