

Features

Use: Indoor
Type of installation: SUSPENDED, CEILING MOUNTED
Emission: DIRECT
Optics: MICROPRISMATIZED
Colour: WHITE
Dimming: DALI2, PUSH
Emergency: NO
L: 1440mm
A: 46mm
H: 70mm
Warranty: 5 years
Weight: 3.5kg

Tech data

Luminaire input power: 31W
Luminaire luminous flux: (3K) 3199lm / (4K) 3290lm
IP: 40
Insulation class: I
No. of driver per product: 1
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 28W
Source luminous flux: 5190lm
Colour temperature: 3000K/4000K
CRI: >80
Colour tolerance: 3 Step MacAdam
LED lifespan: 50000h L90 B10

Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: CAM edilizia - Conforme al Decreto Ministeriale 23 giugno 2022 n.256 e 24 novembre 2025 n.256.

[LYNO: View more product info](#)

COMPLETION ACCESSORIES



LYNO: COPPIA TESTATE BIA

115803.01




LYNO: COPPIA STAFFE FISSAGGIO PLAFONE

115804.99



LYNO: COPPIA KIT SOSP. CAVO L 3M

115805.99



LYNO: STAFFA DI GIUNZIONE

115806.99
