

Features

Use: Indoor
Type of installation: RECESSED INTO PLASTERBOARD
Emission: DIRECT
Optics: OPAL
Beam: 100°
Colour: WHITE
Dimming: WITH ACCESSORY
Emergency: WITH ACCESSORY
L: 160mm
A: 160mm
H: 26mm
Warranty: 5 years
Weight: 0.56kg

Tech data

Luminaire input power: 15W
Luminaire luminous flux: 1475lm
Luminous flux in emergency: 1h: 35% / 3h: 14%
IP: 40
Insulation class: II
Supply voltage: 220-240V 50/60Hz
SELV: Si

Source

Light source: LED
Source power: 13W
Source luminous flux: 1740lm
Colour temperature: 4000K
CRI: >80
LED lifespan: 50000h L80 B20

Compliance


CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1, 2-2

Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.


[View more product info](#)

EMERGENCY ACCESSORIES



KIT EMERGENZA 1H 9V-58V

18002.99



KIT EMERGENZA 3H 9V-58V

18003.99