

## Features

Use: Indoor  
 Type of installation: RECESSED INTO PLASTERBOARD  
 Emission: DIRECT  
 Optics: OPAL  
 Beam: 100°  
 Colour: WHITE  
 Dimming: WITH ACCESSORY  
 Emergency: WITH ACCESSORY  
 L: 160mm  
 A: 160mm  
 H: 26mm  
 Warranty: 5 years  
 Weight: 0.56kg

## Tech data

Luminaire input power: 15W  
 Luminaire luminous flux: 1491lm  
 Luminous flux in emergency: 1h: 35% / 3h: 14%  
 IP: 40  
 Insulation class: II  
 No. of driver per product: 1  
 Supply voltage: 220-240V 50/60Hz  
 SELV: Si

## Source

Light source: LED  
 Source power: 13W  
 Colour temperature: 4000K  
 CRI: >90  
 LED lifespan: 50000h L80 B20

## Compliance

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

## Standards

Photobiological risk: RISK GROUP 0 Certified fixture in EXEMPT GROUP, in accordance with CEI EN 62471:2010-01, IEC TR 62778:2014.  
 CAM edilizia: The product complies with the requirements for public buildings, ministerial decree of 23rd June 2022 n.256.

[View more product info](#)

## DIMMABLE ACCESSORIES

---




ALIM. LED 25W 350MA/2-50V DALI/PUSH

**101333.99**


## EMERGENCY ACCESSORIES

---



KIT EMERGENZA 3H 10V-54V

**18005.99**



KIT EMERGENZA 1H 10V-54V

**18004.99**