



Caractéristiques

Utilisation: Intérieur
Type installation: APPLIQUE MURALE, ENCASTRABLE EN PLAQUE DE PLÂTRE, SUSPENSION, PLAFONNIER, RAIL
Émission: DIRECTE
Optique: OPALE
Couleur: CAFÉ
Variation: ON/OFF
Urgence: NO
L: 2520mm
A: 53mm
H: 69mm
Fabriqué en: ITALY
Garantie: 5 ans
Poids: 8.8kg

Données techniques

Puissance réelle lumineuse: 61.9W
Flux lumineux lumineuse: 4369lm
IP: 40
Classe d'isolation: I
N° de driver par produit: 2
Tension d'alimentation: 220-240V 50/60Hz
SELV: Si

La source

Source lumineuse: LED
Puissance source: 54W
Température couleur: 3000K
IRC: >90
Tolérance couleur: 3 Step MacAdam
Durée de vie LED: 50000h L80 B20

Conformité

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Normes

Risque photobiologique: GROUPE DE RISQUE 0 Équipement certifié dans le GROUPE SANS RISQUE, selon la norme IEC EN 62471:2010-01, IEC TR 62778:2014.
CAM bâtiment: Conforme au CAM EDILIZIA (critères environnementaux minimum) du décret ministériel italien du 23 juin 2022 n.256.

[HERO: Voir plus d'informations sur le produit](#)

HERO

108613.20 + 108906.99

HERO: 54W 3K 2520 CAF + HERO: DIFF. OPALE PER 2520



novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Caractéristiques

Utilisation: Intérieur

Optique: OPALE

L: 2520mm

A: 48mm

H: 6mm

Fabriqué en: ITALY

Garantie: 5 ans

Poids: 0.6kg

Données techniques

IP: 40



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italie
Tél: +39 051 860558 · Fax +39 051 6647859 · E-mail: info@novalux.it · N° TVA IT00536541204 · novalux.com
Entreprise soumise à la direction et à la coordination de SLV GmbH

Cette fiche technique est la propriété de Novalux S.r.l., tous droits réservés. Novalux S.r.l. se réserve le droit d'apporter des modifications sans préavis.
Dernière actualisation: 4/7/2025, 19:14:20

HERO

108613.20 + 108906.99

HERO: 54W 3K 2520 CAF + HERO: DIFF. OPALE PER 2520

ACCESSOIRES COMPLÉMENTAIRES

 Technical drawing of a linear track lighting fixture, model MOD.CIECO 250 CAF. It shows a side view with dimensions: H 135, L 250, W 33. A small detail shows the mounting bracket.	HERO: MOD.CIECO 250 CAF	108676.20
 Technical drawing of a linear track lighting fixture, model MOD.CIECO 1400 CAF. It shows a side view with dimensions: H 135, L 1400, W 33. A small detail shows the mounting bracket.	HERO: MOD.CIECO 1400 CAF	108680.20
 Technical drawing of an angled track lighting fixture, model MOD.CIECO ANG.SX 150 CAF. It shows a side view with dimensions: H 135, L 150, W 33. A small detail shows the mounting bracket.	HERO: MOD.CIECO ANG.SX 150 CAF	108677.20
 Technical drawing of a linear track lighting fixture, model MOD.CIECO 1680 CAF. It shows a side view with dimensions: H 135, L 1680, W 33. A small detail shows the mounting bracket.	HERO: MOD.CIECO 1680 CAF	108681.20
 Technical drawing of a pair of end caps for the track lighting system, model COPPIA TESTATE CAF. It shows two small rectangular components with dimensions: L 15, W 33.	HERO: COPPIA TESTATE CAF	108684.20
 Technical drawing of an angled track lighting fixture, model MOD.CIECO ANG.DX 150 CAF. It shows a side view with dimensions: H 135, L 150, W 33. A small detail shows the mounting bracket.	HERO: MOD.CIECO ANG.DX 150 CAF	108678.20
 Technical drawing of a linear track lighting fixture, model MOD.CIECO 1120 CAF. It shows a side view with dimensions: H 135, L 1120, W 33. A small detail shows the mounting bracket.	HERO: MOD.CIECO 1120 CAF	108679.20

ACCESSOIRES DE MONTAGE

 Technical drawing of a suspension arm for the track lighting system, model SOSPL3000 1PZ. TESTA/CODA. It shows a vertical arm with dimensions: H 12, L 17.	HERO: SOSPL3000 1PZ. TESTA/CODA	108685.99
 Technical drawing of a pair of adaptors for the track lighting system, model COPPIA ADATT. 3P BIA. It shows two small rectangular components.	ALL-TRACK: COPPIA ADATT. 3P BIA	106722.01
 Technical drawing of a power supply kit for the track lighting system, model KIT ALIMENTAZIONE L1200 3P CAF. It shows a cable with dimensions: H 12, L 17.	KIT ALIMENTAZIONE L1200 3P CAF	108919.20



	KIT ALIMENTAZIONE L1200 3P BIA	108919.01
	ALL-TRACK: COPPIA ADATT. 3P NER	106722.02
	HERO: SPESS. CARTONG. 10MM 2PZ.	108689.99
	HERO: SOSP.L3000 1PZ. UNIONE	108686.99
	HERO: STAFFA PARETE "L" CAF	108687.20
	HERO: SOSP.L3000 1PZ TESTA W.G.ALTO	1086A1.99
	KIT ALIMENTAZIONE L3000 3P BIA	108920.01
	HERO: KIT INCASSO LED (1X)	108688.99
	HERO: SOSP.L3000 1PZ UNIONE W.G.ALTO	1086A2.99
	KIT ALIMENTAZIONE L3000 3P CAF	108920.20