



Funcities

Gebruik: Binnenshuis

Type installatie: OPBOUW WAND, INBOUW IN GIPSPLAAT, PENDEL, PLAFOND, RAIL

Emissie: DIRECT

Optiek: OPAAL

Kleur: KOFFIE

Dimmen: ON/OFF

Noodsituatie: NEEN

L: 1960mm

A: 53mm

H: 69mm

Made in: ITALY

Garantie: 5 jaar

Gewicht: 5kg

Technische gegevens

Echt apparaatvermogen: 48.3W

Armatuurlichtstroom: 3340lm

IP: 40

Isolatieklasse: I

Aantal voedingen per armatuur: 2

Voedingsspanning: 220-240V 50/60Hz

SELV: Si

Bron

Lichtbron: LED

Vermogen bron: 42W

Temperatuurkleur: 2700K

CRI: >90

Tolerantie kleur: 3 Step MacAdam

LED levensduur: 50000h L80 B20

Voldoening

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Normen

Fotobiologisch risico: RISICOGROEP 0Gecertificeerd apparaat in een RISICOVRIJE GROEP, in overeenstemming met de normen CEI EN 62471:2010-01, IEC TR 62778:2014.

CAM edilizia (CAM constructie): In overeenstemming met CAM EDILIZIA Ministerieel besluit 23 juni 2022 n.256.

[Bekijk meer informatie over het product](#)

HERO

108604.20 + 108904.99

HERO: 42W 2.7K 1960 CAF + HERO: DIFF. OPALE PER 1960



novalux
ITALIAN LIGHTING DESIGN SINCE 1948



Functies

Gebruik: Binnenshuis

Optiek: OPAAL

L: 1960mm

A: 48mm

H: 6mm

Made in: ITALY

Garantie: 5 jaar

Gewicht: 0.4kg

Technische gegevens

IP: 40



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · P.IVA 00536541204 · novalux.com
Bedrijf onderworpen aan beheer en coördinatie door SLV GmbH

Dit technische gegevensblad is eigendom van Novalux S.r.l., alle rechten voorbehouden. Novalux S.r.l. behoudt zich het recht voor om zonder voorafgaande kennisgeving wijzigingen aan te brengen.
Laatste update: 4/4/2025, 22:44:01

AANVULLENDE ACCESSOIRES

 Technical drawing of a linear track lighting fixture, model MOD.CIECO 250 CAF. It shows a side view with dimensions: H 135, L 250, W 33. A top view shows a width of 33mm.	HERO: MOD.CIECO 250 CAF	108676.20
 Technical drawing of a linear track lighting fixture, model MOD.CIECO 1400 CAF. It shows a side view with dimensions: H 135, L 1400, W 33. A top view shows a width of 33mm.	HERO: MOD.CIECO 1400 CAF	108680.20
 Technical drawing of an L-shaped track lighting fixture, model MOD.CIECO ANG.SX 150 CAF. It shows a side view with dimensions: H 135, L 150, W 33. A top view shows an L-shape with a width of 150mm.	HERO: MOD.CIECO ANG.SX 150 CAF	108677.20
 Technical drawing of a linear track lighting fixture, model MOD.CIECO 1680 CAF. It shows a side view with dimensions: H 135, L 1680, W 33. A top view shows a width of 33mm.	HERO: MOD.CIECO 1680 CAF	108681.20
 Technical drawing of a pair of end caps for the track lighting system, model COPPIA TESTATE CAF. It shows two small rectangular components with dimensions: H 135, L 33, W 33.	HERO: COPPIA TESTATE CAF	108684.20
 Technical drawing of an L-shaped track lighting fixture, model MOD.CIECO ANG.DX 150 CAF. It shows a side view with dimensions: H 135, L 150, W 33. A top view shows an L-shape with a width of 150mm.	HERO: MOD.CIECO ANG.DX 150 CAF	108678.20
 Technical drawing of a linear track lighting fixture, model MOD.CIECO 1120 CAF. It shows a side view with dimensions: H 135, L 1120, W 33. A top view shows a width of 33mm.	HERO: MOD.CIECO 1120 CAF	108679.20

MONTAGE ACCESSOIRES

 Technical drawing of a suspension arm for the track lighting system, model SOSPL3000 1PZ. TESTA/CODA. It shows a vertical arm with dimensions: H 12, L 17.	HERO: SOSPL3000 1PZ. TESTA/CODA	108685.99
 Technical drawing of a pair of adaptors for the track lighting system, model COPPIA ADATT. 3P BIA. It shows two small components with dimensions: H 135, L 33, W 33.	ALL-TRACK: COPPIA ADATT. 3P BIA	106722.01
 Technical drawing of a power supply kit for the track lighting system, model KIT ALIMENTAZIONE L1200 3P CAF. It shows a cable with dimensions: H 135, L 1200, W 33.	KIT ALIMENTAZIONE L1200 3P CAF	108919.20
 Technical drawing of a power supply kit for the track lighting system, model KIT ALIMENTAZIONE L1200 3P BIA. It shows a cable with dimensions: H 135, L 1200, W 33.	KIT ALIMENTAZIONE L1200 3P BIA	108919.01



	ALL-TRACK: COPPIA ADATT. 3P NER	106722.02
	HERO: SPESS. CARTONG. 10MM 2PZ.	108689.99
	HERO: SOSPL3000 1PZ. UNIONE	108686.99
	HERO: STAFFA PARETE "L" CAF	108687.20
	HERO: SOSPL3000 1PZ TESTA W.G.ALTO	1086A1.99
	KIT ALIMENTAZIONE L3000 3P BIA	108920.01
	HERO: KIT INCASSO LED (1X)	108688.99
	HERO: SOSPL3000 1PZ UNIONE W.G.ALTO	1086A2.99
	KIT ALIMENTAZIONE L3000 3P CAF	108920.20