

Funcities

Gebruik: Binnenshuis
Type installatie: INBOUW IN GIPSPLAAT
Emissie: DIRECT
Optiek: MICRO-OPTIEKEN
Kleur: ZWART
Dimmen: ON/OFF
Noodsituatie: NEEN
L: 1428mm
A: 61mm
H: 68mm
Made in: ITALY
Garantie: 5 jaar
Gewicht: 4.2kg

Technische gegevens

Echt apparaatvermogen: 40.5W
Armatuurlichtstroom: 4020lm
IP: 40
Isolatieklasse: I
Aantal voedingen per armatuur: 1
Voedingsspanning: 220-240V 50/60Hz
UGR: <19
SELV: Si

Bron

Lichtbron: LED
Vermogen bron: 36W
Temperatuurkleur: 4000K
CRI: >90
Tolerantie kleur: 3 Step MacAdam
LED levensduur: 50000h L80 B20

Voldoening

CEI EN 60598-1:2021 + A11:2023, CEI EN 60598-2-1:2022, CEI EN 60598-2-2:2012

Normen

Fotobiologisch risico: RISICOGROEP 0Gecertificeerd apparaat in een RISICOVRIJE GROEP, in overeenstemming met de normen CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia (CAM constructie): In overeenstemming met CAM EDILIZIA Ministerieel besluit 23 juni 2022 n.256.

Gemiddelde luminantie

Luminantielimit in omgevingen met VDT's: Minder dan 3000 cd/m² voor hoeken > 65° (volgens EN 12464-1:2011).

[Bekijk meer informatie over het product](#)










HERO C

108824.02

novalux
ITALIAN LIGHTING DESIGN SINCE 1948

AANVULLENDE ACCESSOIRES

 <p>Technical drawing showing a perspective view of a rectangular lighting fixture with dimensions L, W, and H. A small inset shows a top-down view with dimensions L, W, and H. Below the drawing are the dimensions: H 20, L 138, W 55.</p>	HERO C: MOD.CIECO 250 NE	108852.02
 <p>Technical drawing showing a perspective view of an L-shaped lighting fixture with dimensions L, W, and H. A small inset shows a top-down view with dimensions L, W, and H. Below the drawing are the dimensions: H 20, L 100-150, W 55.</p>	HERO C: MOD.CIECO ANG.SX 150 NE	108853.02
 <p>Technical drawing showing a perspective view of an L-shaped lighting fixture with dimensions L, W, and H. A small inset shows a top-down view with dimensions L, W, and H. Below the drawing are the dimensions: H 20, L 100-150, W 55.</p>	HERO C: MOD.CIECO ANG.DX 150 NE	108854.02
 <p>Technical drawing showing a perspective view of a rectangular lighting fixture with dimensions L, W, and H. A small inset shows a top-down view with dimensions L, W, and H. Below the drawing are the dimensions: H 20, L 138, W 55.</p>	HERO C: MOD.CIECO 1120 NE	108855.02
 <p>Technical drawing showing a perspective view of a rectangular lighting fixture with dimensions L, W, and H. A small inset shows a top-down view with dimensions L, W, and H. Below the drawing are the dimensions: H 20, L 138, W 55.</p>	HERO C: MOD.CIECO 1400 NE	108856.02
 <p>Technical drawing showing a perspective view of a rectangular lighting fixture with dimensions L, W, and H. A small inset shows a top-down view with dimensions L, W, and H. Below the drawing are the dimensions: H 20, L 138, W 55.</p>	HERO C: MOD.CIECO 1680 NE	108857.02
 <p>Technical drawing showing a perspective view of a pair of rectangular lighting fixtures with dimensions L, W, and H. A small inset shows a top-down view with dimensions L, W, and H. Below the drawing are the dimensions: H 20, L 2, W 55.</p>	HERO C: COPPIA TESTATE NE	108860.02



Novalux S.r.l. via Marzabotto, 2 40050 Funo di Argelato (BO) Italy
Tel: +39 051 860558 · Fax +39 051 6647859 · Mail: info@novalux.it · P.IVA 00536541204 · novalux.com
Bedrijf onderworpen aan beheer en coördinatie door SLV GmbH

Dit technische gegevensblad is eigendom van Novalux S.r.l., alle rechten voorbehouden. Novalux S.r.l. behoudt zich het recht voor om zonder voorafgaande kennisgeving wijzigingen aan te brengen.
Laatste update: 4/4/2025, 22:27:38