

CREP




Apparecchio LED per installazione a plafone o ad incasso in battuta in controsoffitto. Temperatura di colore delle sorgenti selezionabile con selettore sul retro dell'apparecchio in 3000K, 4000K o 5400K. Disponibile in due dimensioni, potenza totale settabile tra tre disponibili.

Corpo in policarbonato e schermo diffusore in polistirene opale. Staffa di installazione in acciaio. Molle in acciaio armonico per fissaggio su controsoffitto di spessore fino a 15 mm, che permettono la regolazione in funzione della dimensione del foro da incasso disponibile. Alimentazione elettronica inclusa, integrata nel corpo dell'apparecchio.

LED fixture for ceiling or recessed installation in false ceiling. Source color temperature, selectable with selector on the back of the fixture in 3000K, 4000K or 5400K.

Two sizes are available, total power adjustable between three available. Polycarbonate body and diffuser screen in opal polystyrene. Steel installation bracket. Springs in harmonic steel for fastening to false ceiling thickness up to 15 mm, which allow adjustment according to the size of the recessed hole available. Electronic power supply included, integrated in the body of the fixture.



CREP TONDO CREP ROUND

| | Ø (mm) | H (mm) | |
|-----------------|--------|--------|------------------|
| 10W / 13W / 16W | 235 | 16 | 107501.01 |
| 16W / 20W / 22W | 300 | 20 | 107503.01 |

Potenza e temperatura di colore delle sorgenti selezionabili con selettore


Power and source color temperature selectable with selector

CREP Ø235mm

| LED colour | 10W | 13W | 16W |
|------------|------|------|---------|
| 3000K | 1094 | 1387 | 1642 lm |
| 4000K | 1173 | 1516 | 1826 lm |
| 5400K | 1134 | 1447 | 1696 lm |

CREP Ø300mm

| LED colour | 16W | 20W | 22W |
|------------|------|------|---------|
| 3000K | 1682 | 2015 | 2191 lm |
| 4000K | 1896 | 2252 | 2483 lm |
| 5400K | 1749 | 2093 | 2280 lm |



CREP QUADRATO CREP SQUARE

| | L (mm) | H (mm) | |
|-----------------|--------|--------|------------------|
| 10W / 13W / 16W | 235 | 16 | 107502.01 |
| 16W / 20W / 22W | 300 | 20 | 107504.01 |

Potenza e temperatura di colore delle sorgenti selezionabili con selettore

Power and source color temperature selectable with selector

CREP L.235mm

| LED colour | 10W | 13W | 16W |
|------------|------|------|---------|
| 3000K | 1094 | 1387 | 1642 lm |
| 4000K | 1173 | 1516 | 1826 lm |
| 5400K | 1134 | 1447 | 1696 lm |

CREP L.300mm

| LED colour | 16W | 20W | 22W |
|------------|------|------|---------|
| 3000K | 1709 | 2061 | 2233 lm |
| 4000K | 1850 | 2260 | 2470 lm |
| 5400K | 1800 | 2163 | 2325 lm |




Selettore temperatura di colore delle sorgenti 3000K, 4000K o 5400K.

Color temperature selector 3000K, 4000K, or 5400K.



Selettore potenza totale 10W, 13W o 16W. 16W, 20W o 22W.

Total power selector 10W, 13W or 16W. 16W, 20W or 22W.



Molle regolabili per installazione a controsoffitto,removibili per installazione a plafone.

Adjustable springs for ceiling installation, removable for ceiling installation.