





C R E P

CREP



Apparecchio LED per installazione a plafone o ad incasso in battuta in controsoffitto. Temperatura di colore delle sorgenti selezionabile con selettore sul retro dell'apparecchio in 3000K, 4000K o 5400K. Disponibile in due dimensioni, potenza totale settabile tra tre disponibili. Corpo in policarbonato e schermo diffusore in polistirene opale. Staffa di installazione in acciaio. Molle in acciaio armonico per fissaggio su controsoffitto di spessore fino a 15 mm, che permettono la regolazione in funzione della dimensione del foro da incasso disponibile. Alimentazione elettronica inclusa, integrata nel corpo dell'apparecchio.


LED fixture for ceiling or recessed installation in false ceiling. Source color temperature, selectable with selector on the back of the fixture in 3000K, 4000K or 5400K. Two sizes are available, total power adjustable between three available. Polycarbonate body and diffuser screen in opal polystyrene. Steel installation bracket. Springs in harmonic steel for fastening to false ceiling thickness up to 15 mm, which allow adjustment according to the size of the recessed hole available. Electronic power supply included, integrated in the body of the fixture.



CREP TONDO
CREP ROUND

	Ø (mm)	H (mm)	□
10W / 13W / 16W	235	16	107501.01
16W / 20W / 22W	300	20	107503.01

Potenza e temperatura di colore delle sorgenti selezionabili con selettore	CREP Ø235mm			CREP Ø300mm				
	LED colour	10W	13W	16W	LED colour	16W	20W	22W
Power and source color temperature selectable with selector	3000K	1094	1387	1642	3000K	1682	2015	2191
	4000K	1173	1516	1826	4000K	1896	2252	2483
	5400K	1134	1447	1696	5400K	1749	2093	2280



CREP QUADRATO
CREP SQUARE

	L (mm)	H (mm)	□
10W / 13W / 16W	235	16	107502.01
16W / 20W / 22W	300	20	107504.01

Potenza e temperatura di colore delle sorgenti selezionabili con selettore	CREP L.235mm			CREP L.300mm				
	LED colour	10W	13W	16W	LED colour	16W	20W	22W
Power and source color temperature selectable with selector	3000K	1094	1387	1642	3000K	1709	2061	2233
	4000K	1173	1516	1826	4000K	1850	2260	2470
	5400K	1134	1447	1696	5400K	1800	2163	2325




Selettore temperatura di colore delle sorgenti 3000K, 4000K o 5400K.

Color temperature selector 3000K, 4000K, or 5400K.



Selettore potenza totale 10W, 13W o 16W. 16W, 20W o 22W.

Total power selector 10W, 13W or 16W. 16W, 20W or 22W.



Molle regolabili per installazione a controsoffitto, removibili per installazione a plafone.

Adjustable springs for ceiling installation, removable for ceiling installation.