



H U L K

NEW HULK




Apparecchio LED IP65 per installazione a soffitto o parete. Provisto di selettore per la temperatura di colore delle sorgenti LED (3000K/4000K/6500K) e alimentatore elettronico ON/OFF 220-240V, 50/60 Hz incluso, settabile su tre potenze totali (11W/14W/16W). Corpo in PC bianco, diffusore in policarbonato opale e anello di chiusura a scatto in ABS bianco, progettato per garantire la corretta pressione sulla guarnizione di tenuta. IK08. Predisposizione per l'inserimento a scatto di accessori kit inverter-batteria 1H/24H e/o centralina con sensore di luminosità e presenza a microonde, entrambi installabili mediante connessione rapida, anche dopo la messa in opera iniziale.

LED fixture with IP65 rating for ceiling or wall installation. Equipped with a selector for the LED source color temperature (3000K/4000K/6500K) and ON/OFF electronic driver 220-240V, 50/60 Hz included, adjustable to three total power levels (11W/14W/16W). White PC body, opal polycarbonate diffuser, and white ABS snap-on closing ring, designed to ensure proper pressure on the sealing gasket. IK08. Prepared for snap-in installation of inverter-battery kit 1H/24H and/or control unit with brightness and microwave presence sensor, both installable via quick connection, even after initial installation.



CEILING
SUSPENSION




	Ø (mm)	H (mm)	□
11W / 14W / 16W	300	50	115401.01

Potenza e temperatura di colore delle sorgenti selezionabili con selettore.	11W	14W	16W	3000K	4000K	6500K
Power and source color temperature selectable with selector.	11W	14W	16W	1287 lm	1383 lm	1370 lm
				1560 lm	1709 lm	1681 lm
				1779 lm	1975 lm	1920 lm

HULK


ACCESSORI
ACCESSORIES



KIT EMERGENZA 1H/24H
1H/24H EMERGENCY KIT

115402.99

Flusso di emergenza Emergency Flux	1h
HULK 11W	8%
HULK 14W	6%
HULK 16W	5%



CENTRALINA CON SENSORE DI LUMINOSITÀ E PRESENZA MW
Programmabile tramite Dip-Switches. Non idonea per impianti con circuito di emergenza con differenziale separato.

115403.99

CONTROL UNIT WITH BRIGHTNESS AND MW PRESENCE SENSOR
Programmable via DIP switches. Not suitable for systems with emergency circuits using a separate residual-current device.

Selettore potenza totale
11W/14W/16W

Total power selector
11W/14W/16W

Centralina con sensore di luminosità e presenza a microonde.

Control unit with brightness and microwave presence sensor.



Kit inverter-batteria 1H/24H

Inverter-battery kit 1H/24H

Selettore temperatura di colore delle sorgenti
3000K/4000K/6500K

Light source color temperature selector
3000K/4000K/6500K