




LYNO



Apparecchio LED lineare ad emissione diretta, installabile a sospensione stand alone o in fila continua, oppure a plafone solo stand alone. Sorgenti LED CCT con temperatura di colore selezionabile tramite selettore in 3000K/4000K. Alimentatore elettronico integrato ON/OFF o dimmerabile DALI/PUSH 220-240V, 50/60 Hz, provvisto di DIP-Switch per settare la potenza totale da 20W a 31W. Disponibili due versioni con diffusore in policarbonato incluso: una con schermo opale e una con schermo prismaticizzato UGR<19. Profilo e testate in lega di alluminio verniciato bianco e schermo cieco superiore in materiale plastico bianco. Testate terminali, giunti di unione moduli (solo per installazione a sospensione) ed accessori di installazione da ordinare separatamente.

Linear LED fixture with direct emission, suitable for stand-alone suspended installation or continuous row mounting, as well as for surface-mounted installation in stand-alone configuration only. CCT LED sources with selectable colour temperature via selector switch (3000K / 4000K). Integrated electronic driver ON/OFF or dimmable DALI/PUSH, 220-240V, 50/60 Hz, equipped with DIP-switch to set the total power from 20W to 31W. Two versions available with included polycarbonate diffuser: one with opal screen and one with prismatic screen, UGR <19. Extruded aluminium profile and end caps finished in white paint, with upper blind cover in white plastic material. End caps, module connecting joints (for suspended installation only) and installation accessories to be ordered separately.




**LYNO OPALE**  
Schermo in policarbonato opale incluso.

**LYNO OPAL**  
Opal polycarbonate diffuser included.

L (mm)		<input type="checkbox"/>	3000K-4000K
1440	28W	<b>115801.01</b>	vedi tabella flussi

<b>DALI-PUSH</b>			
L (mm)		<input type="checkbox"/>	3000K-4000K
1440	28W	<b>115807.01</b>	3433 lm - 3531 lm



**LYNO MICROPRISMATIZZATO**  
Schermo in policarbonato microprismaticizzato incluso.

**LYNO MICROPRISMATIC**  
Microprismatic polycarbonate diffuser included.

L (mm)		<input type="checkbox"/>	3000K-4000K
1440	28W	<b>115802.01</b>	vedi tabella flussi

<b>DALI-PUSH</b>			
L (mm)		<input type="checkbox"/>	3000K-4000K
1440	28W	<b>115808.01</b>	3199 lm - 3290 lm



**LYNO OPALE**

W tot	mA	3000K	4000K
31	1050	3433 lm	3531 lm
29	1000	3280 lm	3373 lm
28	950	3127 lm	3216 lm
26	900	2974 lm	3059 lm
24	850	2820 lm	2901 lm
22	800	2667 lm	2743 lm
21	750	2515 lm	2586 lm
20	700	2361 lm	2428 lm

**LYNO MICROPRISMATIZZATO**

W tot	mA	3000K	4000K
31	1050	3199 lm	3290 lm
29	1000	3056 lm	3143 lm
28	950	2914 lm	2997 lm
26	900	2771 lm	2850 lm
24	850	2628 lm	2703 lm
22	800	2485 lm	2556 lm
21	750	2343 lm	2410 lm
20	700	2200 lm	2263 lm

TESTATE TERMINALI (2 pz)	<input type="checkbox"/>
END CAPS (2 pcs)	<b>115803.01</b>

STAFFA DI GIUNZIONE Montaggio in fila continua possibile solo per installazioni a sospensione.	<input type="checkbox"/>
	<b>115806.01</b>

JOINING BRACKET  
Continuous row installation possible  
only for suspended installations.

Il sistema di aggancio a leve  
autobloccanti garantisce il preciso  
accoppiamento dei profili, elevata  
stabilità strutturale e affidabilità nel  
tempo.


The self-locking lever coupling system  
ensures precise mating of the profiles,  
high structural stability, and long-term  
reliability.



STAFFE PER INSTALLAZIONE A PLAFONE (2 pz)	<input type="checkbox"/>
CEILING MOUNTING BRACKETS (2 PCS)	<b>115804.01</b>

CAVI DI SOSPENSIONE (2 pz) Prevedere 2 cavi per ciascun profilo.	<input type="checkbox"/>
	<b>115805.01</b>

SUSPENSION CABLES (2 PCS)  
Provide 2 cables for each profile.



KIT DI ALIMENTAZIONE Cavo con guaina trasparente	<input type="checkbox"/>	L (mm)	Cavo / Cable (mm <sup>2</sup> )
<b>108920.01</b>		3000	3x1,5
POWER SUPPLY KIT Cable with transparent sheath	<b>108922.01</b>	3000	5x1,5

