


PROFILED TONDO



Profilo dissipante per Strip LED in lega di alluminio verniciata bianca, testate di chiusura in polimero termoplastico, schermo diffusore ad inserimento a scatto in PMMA opale. Schermo diffusore e testate di chiusura inclusi.
Kit di sospensione, staffe per installazione a parete, strip LED e alimentatore 24Vdc da ordinare a parte.
Non esporre a intemperie o luce solare diretta e non inserire in materiale isolante.


Dissipating profile for Strip LED made of white powder coated aluminium alloy, end caps made of thermoplastic polymer, screen made of opal finish PMMA. Diffuser and end caps included.
Suspension kit, wall brackets, strip LED and driver 24Vdc to be ordered separately.
Do not expose to bad weather or direct sunlight and do not insert into insulating material.



CODE	☐	L (mm)	Diffuser
105401.01		2000	Opale / Opal

PROFILED TONDO


ACCESSORI ACCESSORIES



KIT SOSPENSIONE
Cavi in acciaio L. 2000 mm
con terminale in ottone cromato.

SUSPENSION KIT
Steel cables L. 2000 mm
with tile pipes made of chromed brass.


CODE		L (mm)
105403.99		2000



**KIT DI ALIMENTAZIONE
PER SOSPENSIONE**
rosone ad incasso in controsoffitto
di spessore da 5 a 15 mm.
Cavo con guaina bianca.

POWER SUPPLY FOR SUSPENSION
recessed ceiling mounted canopy
for thickness from 5 up to 15 mm.
Cable with white sheath.

CODE	☐	L (mm)	Cavo / Cable (mm²)
103319.01		1200	3x0,75




**KIT DI ALIMENTAZIONE
PER SOSPENSIONE**
rosone a plafone.
Cavo con guaina bianca.

**POWER SUPPLY
FOR SUSPENSION**
ceiling mounted canopy.
Cable with white sheath.

CODE	☐	L (mm)	Cavo / Cable (mm²)
103320.01		1200	3x0,75

PROFILED TONDO

ACCESSORI ACCESSORIES



STAFFE PARETE (2 pz.)
WALL BRACKETS (2 pcs)

CODE

**105402.01**

GIUNTO LINEARE (1 pz.)
LINEAR JUNCTION (1 pc)

CODE


105414.99

TESTATE DI CHIUSURA (2 pz.)
Da prevedere in caso di utilizzo
di sezioni di profilo tagliate in opera.

CODE

**105404.01**

END CAPS (2 pcs)
To be used for sections
of profile cut on site.



STRIP LED

Pag. 204

Per ottenere uniformità di luminanza nelle
installazioni con schermo a vista, utilizzare strip
LED 19,2W/m, 22W/m, 8,8W/m (24Vdc),
o 17W/m (48Vdc).

To achieve luminance uniformity when installed
with clearly visible diffusers, the strip LED to be
used is 19,2W/m, 22W/m, 8,8W/m (24Vdc),
or 17W/m (48Vdc).