





LUCKY EVO

Essenziale nel design, il sistema LED Novalux LUCKY EVO si presta a numerose applicazioni ed è in grado di integrare, con armonia, illuminazione e contesto architettonico. Le diverse tipologie di installazione, e la vasta gamma di accessori, rendono LUCKY EVO un apparecchio luminoso perfetto per qualunque settore, dal residenziale al commerciale, dal business al retail.

With an essential design, the Novalux LED system LUCKY EVO is suitable for numerous applications and is able to combine lighting and architectural context in a harmonious way. The different types of installation, and the wide range of accessories, make LUCKY EVO an ideal luminaire for any sector, from residential to commercial, from business to retail.

LUCKY EVO

- **SCHERMO OPALE O SCHERMO CON FILM MICROSTRUTTURATO UGR<19 ANTIABBAGLIAMENTO FINO A L. 6 m**
OPAL DIFFUSER OR ANTI-GLARE DIFFUSER WITH MICROSTRUCTURED FILM UP TO L. 6 m

- **CONNETTORI RAPIDI PER FILA CONTINUA**
RAPID CONNECTORS FOR CONTINUOUS LINE INSTALLATION
- **FISSAGGIO MAGNETICO DEL VANO OTTICO CON PCB LED**
OPTICAL PART WITH LED PCB INSTALLED ON MAGNETS





**DIFFUSORE OPALE**


Schermo diffusore ad incastro a filo in policarbonato opale.

OPAL DIFFUSER

Opal polycarbonate flush diffuser.

Diffusore opale lineare/Linear opal diffuser

L (mm)	3000K	4000K	CODE
1125	2077 lm	2177 lm	18742.99
1406	2597 lm	2721 lm	18743.99
1687	3116 lm	3265 lm	18774.99
1968	3636 lm	3809 lm	100557.99
2249	4155 lm	4354 lm	100558.99
2530	4675 lm	4898 lm	100559.99
2811	5194 lm	5442 lm	100560.99
*6000	-	-	1005A0.99

**DIFFUSORE UGR<19**

Schermo diffusore per il controllo dell'abbagliamento, ad incastro a filo in policarbonato trasparente + film microstrutturato.

UGR<19 DIFFUSER

Anti-glare flush diffuser, made of transparent polycarbonate + micro-structured film.

UGR
<19

Diffusore UGR<19 lineare/Linear UGR<19 diffuser

L (mm)	3000K	4000K	CODE
1125	1970 lm	2004 lm	100573.99
1406	2462 lm	2504 lm	100574.99
1687	2955 lm	3005 lm	100575.99
1968	3448 lm	3507 lm	100576.99
2249	3941 lm	4008 lm	100577.99
2530	4433 lm	4509 lm	100578.99
2811	4925 lm	5009 lm	100579.99
*6000	-	-	100581.99

* Schermo 6m consigliato per installazioni in fila continua
6m screen recommended for continuous line installations


Diffusore opale angolare 90°/90° corner opal diffuser

L (mm)	3000K	4000K	CODE
592x592	2077 lm	2176 lm	18744.99

Diffusore UGR<19 angolare 90°/90° corner UGR<19 diffuser


L (mm)	3000K	4000K	CODE
592x592	1970 lm	2003 lm	100580.99

LUCKY EVO


ACCESSORI
ACCESSORIES

TESTATE TERMINALI (2 pz.)


END CAPS (2 pcs)

CODE **18750.01** .02KIT DI GIUNZIONE
Meccanica-elettrica.JUNCTION KIT
Mechanical-electrical.


CODE

18751.99KIT INCASSO FRAMELESS (2 pz.)
Per cartongesso H 12 mm
n°1 kit per profilo lineare fino a L 2249 mmKIT FRAMELESS RECESSED
INSTALLATION (2 pcs)
For H 12 mm plasterboard
n°1 kit for linear profile up to L 2249 mm


CODE

18752.99KIT INCASSO FRAMELESS (3 pz.)
Per cartongesso H 12 mm
n°1 kit per profilo lineare L 2530 mm,
L 2811 mm e per profilo angolare.KIT FRAMELESS RECESSED
INSTALLATION (3 pcs)
For H 12 mm plasterboard
n°1 kit for linear profile L 2530 mm,
L 2811 mm and for corner profile.


CODE

1005A1.99SPESSORE (4 pz.)
Per cartongesso H 10 mm inserire 2 pz in
corrispondenza di ciascuna staffa da incasso.PLASTIC SPACER (4 pcs)
For H 10 mm plasterboard put 2 pcs for each
bracket for recessed installation.

CODE

18753.99STAFFA PARETE (1 pz.)
n°2 per profilo lineare fino a L 2249 mm,
N°3 per profilo L 2530 mm e L 2811 mm.WALL BRACKET (1 pc)
n°2 for linear profile up to L 2249 mm,
n°3 for profile L 2530 mm and L 2811 mm.CODE **1005A2.01** .02


LUCKY EVO

ACCESSORI
ACCESSORIES

KIT DI ALIMENTAZIONE

POWER SUPPLY KIT

CODE	<input type="checkbox"/>	<input checked="" type="checkbox"/>	L (mm)	Cavo / Cable (mm ²)
108919.01			1200	3x1,5
108920.01			3000	3x1,5
108921.01			1200	5x1,5
108922.01			3000	5x1,5




CAVO DI SOSPENSIONE (1 pz)

Da inserire a inizio e fine linea continua e 2 pz per installazione singola.
1 pz aggiuntivo per fissaggio centrale dei profili L 2530 mm, L 2811 mm e angolare.
In acciaio, regolabile.

SUSPENSION CABLE (1 pc)

For both ends of a running line and 2 pcs for single fixture.
1 pc for central suspension of L 2530 mm and L 2811 mm linear profiles and corner profile.
Made of steel, adjustable.

CODE	L (mm)
108685.99	3000




CAVO DI SOSPENSIONE (1 p.z)

Per unione profili
in acciaio, regolabile.

SUSPENSION CABLES (1 pc)

For profiles junction
made of steel, adjustable.

CODE	L (mm)
18757.99	3000

COPPIA DI ADATTATORI
PER BINARIO ALL-TRACKCOUPLE OF ADAPTORS
FOR ALL-TRACK

CODE	<input type="checkbox"/>	<input checked="" type="checkbox"/>	VERSION
106722.01			3P
106723.01			3P+DALI

